

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 700536

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 7 only, T30-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Page 7129)

Set a post, from which
A Balm 12" dia., bears N.63°W., 600 lks. dist.
Made a mound, there being no timber convenient.

Ben B. Irving, Deputy, Douglas Co. Surveyor - Wit: L.H. Smick; N.E. Richardson; Allen Moore - April/May 1929 - M 1-61; C.S. File 1/65 A and B; "old" cor. Bk. Page 183

NOTE: The records of corner descriptions of the Public Survey Office at Portland does not agree with corners as found on ground. Remainder of field notes check reasonably close. After consultation with Dist. Attorney and Co. Surveyor, and in view of the fact that no corners in field checked records and that age of corners corresponded with original work, it was decided to use field corners as the true corner and they were renewed accordingly.

Set by proportional measurement. Drove 2" x 24" Pipe, 24" under ground with wooden plug.
An Apple 12" dia., bears N.15°E., 18 lks. scribed ¼ S7 CS BT.
A B.Oak 57" dia., bears S.45°W., 237 lks. scribed ¼ S7 CS BT.

Doug. County Surveyors Office - James W. Byron, Deputy - Mike Darby; Jim Halterman - Oct. 1963 - C.S. File 53/26-18

Found - 2" I.P. 24" under. Neither BT standing.
Do find roots of NE BT.
Set Brass cap alongside I.P. and Mkd: County Surveyors Office
1963 W.¼ S7 T30S R5W & 6W.
Cap set flush. (See sketch in CS file for B.Cap relationship to buildings.)

5/2011: Fd. 1929 Corner position, calculated from SW Cor. of old dryer Bldg per CS 53/26 - See M162-47 for Greg Lang's proportioned, computed position.