

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 700540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 12 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Volume 17 Page 7196)

Set quarter sec. post around which a small mound of stones was raised, no trees near.

Ben B. Irving, Deputy, Douglas Co. Surveyor - Wit: L.H. Smick; N.E. Richardson; Allen Moore - April/May 1929 - M 1-61; C.S. File 1/65 A and B; "old" cor. Bk. Page 183

NOTE: The records of corner descriptions of the Public Survey Office at Portland does not agree with corners as found on ground. Remainder of field notes check reasonably close. After consultation with Dist. Attorney and Co. Surveyor, and in view of the fact that no corners in field checked records and that age of corners corresponded with original work, it was decided to use field corners as the true corner and they were renewed accordingly.

Set by proportional measurement, a 1" x 36" Galv. I.Pipe driven 26" under ground in plowed field (shoe from grain drill laid on top), from which
 An Apple 12" dia., bears S.10°W., 244 lks. scribed ¼ S12 CS BT.

5/2011: Fd. 1929 1" IP for ¼ Cor. - See M162-47 for Greg Lang's proportioned, computed position.