

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 910020

PRIMARY CORNER DESCRIPTION Cor. #4 M.S. #305

Alias _____ Description Cor. #2 Triangle claim

Alias _____ Description Cor. #4 Oregon claim

Alias _____ Description _____

Alias _____ Description _____

Survey by W.F. Briggs, U.S. Deputy Mineral Surveyor For:
Samuel P. Parmly, Ashley Consolidated Nickel Mines - Survey,
Nov. 5, 1895 (DCSO records Vol. 28 Page(s) 11845; 11847;
11848)

Set post 4½ ft. long, 4 ins. sq., 12" in the ground, with
mound of stone, marked No 2 M.S. 305; from which
Old location corner bears N.10°E., 12 ft.
A Fir 12" dia., bears S.11°E., 84 lks. dist. mkd. No 2
M.S. 305 BT.

(same surveyor, Pg. 11847)
Set a post, 4½ ft. long 4" sq. 12" in the ground, with mound
of stone marked No 4 M.S. 305; from which
A Fir 12" dia., bears S.11°E., 84 lks. mkd. No 4 M.S. 305
BT.
A Fir 6" dia., bears N.68°E., 23 lks. dist., mkd. No 4
M.S. 305 BT.
Old location corner bears N.10°E., 12 ft.

John H. Markham, Jr. - For: Hanna Coal & Ore Co. - Wit: G.D.
Myers; E.D. Jenks - July/Aug. 1957 - C.S. File 42/288-15

Kitchell M.S. 305 Corner #2 and #4 which are common, Sec. 18,
as determined by O.B.T. and old monument. At a point 576.0
ft. S.45°W., from corner 3 & 5, I found old post in mound of
stone. A burnt out stump hole bears N.68°E., 14.2 ft.
At corner point Set brass cap in concrete marked M.S. 2 & 4,
T30S, from which
A 7" Fir bears S.11°W., 35.5 ft. mkd. M.S. 305 BT.
A 8" Fir bears N.46°W., 19.7 ft. mkd. M.S. 305 BT.