

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 910040

PRIMARY CORNER DESCRIPTION Cor. #3 M.S. #305

Alias \_\_\_\_\_ Description Cor. #3 Oregon claim

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Survey by W.F. Briggs, U.S. Deputy Mineral Surveyor For:  
Samuel P. Parmly, Ashley Consolidated Nickel Mines - Survey  
Nov. 5, 1895 (DCSO records Vol. 28 Page(s) 11846; 11848;  
11849)

-----  
Set post, 4½ ft. long, 4" sq., 12" in the ground, with mound  
of stone marked No 3 M S 305; from which

A Pine 16" dia., bears S.72½°E., 84 lks. dist., mkd. No 3  
M.S. 305 BT.

A Pine 36" dia., bears North 13 lks. dist., mkd. No 3 M.S.  
305 BT.

Old location post not found, probably destroyed by fire.

John H. Markham, Jr. - For: Hanna Coal & Ore Co. - Wit: G.D.  
Myers; E.D. Jenks - July/Aug. 1957 - C.S. File 42/288-14

-----  
Kitchell M.S. #305 Corner #3, Sec. 18 as det. by O.B.T.

A 30" Pine bears North 8.6 ft. O.B.T. found scribe.

A 42" Pine snag bears S.72½°E., 56.5 ft. O.B.T.

At corner point found large pile of stones and set brass cap  
in concrete marked M.S. 305 #3 T30S R6W 2880 1957, from  
which:

A 10" Fir bears S.53°E., 11.5 ft. mkd. M.S. 3 BT.

A 8" Fir bears S.19°E., 22.9 ft. mkd. M.S. 3 BT.

A 27" Pine bears N.60½°W., 33.1 ft. mkd. M.S. 3 BT.