

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 910050

PRIMARY CORNER DESCRIPTION Cor. #2 + 1 M.S. #305

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by W.F. Briggs, U.S. Deputy Mineral Surveyor - For:
Ashley Consolidated Nickel Mines - under instructions dated
Oct. 29, 1895 - Survey, Nov. 5, 1895 (DCSO records Vol. 28
Page(s) 11846; 11848; 11849;)

Set post, 4½ ft. long, 4" sq. 12" in the ground, with mound
of stone, marked No. 2 + 1 M.S. 305, at point of
intersection; from which
Southeast corner of Cobb's land bears South, 1238 ft.
dist.

John H. Markham, Jr. - For: Hanna Coal & Ore Co. - Wit: G.D.
Myers; E.D. Jenks - Jul/Aug. 1957 - C.S. File 42/288-12

As determined by field notes
A 30" Fir S.56°E., 57.0 ft., found scribe.
At a point 233.0 ft., S.45°E., from corner #3, I set brass
cap in concrete mkd. M.S. 305 2+1 T30S R6W 2880 1957, from
which:
A 5" Cedar bears S.33°W., 17.0 ft. mkd. M.S. 2+1 BT.
A 10" Pine bears N.24°E., 6.7 ft. mkd. M.S. 2+1 BT.