

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 910060

PRIMARY CORNER DESCRIPTION Cor. #2 M.S. #305

Alias 918024 Description Cor. #2 Emerald M.S. #186

Alias _____ Description Cor. #2 Oregon

Alias _____ Description _____

Alias _____ Description _____

Survey by W.F. Briggs, Deputy Mineral Surveyor For: Edson Adams & Harvey Brown - Survey, Nov. 9, 1888 (DCSO records Vol. 28 Page(s) 11839;)

Set post, 4 ft. long, 4" sq. 18" in the ground, with monument of stone alongside, marked E. M. C. Cor No 2; from which
A Pine 14" dia., bears N.75°E., 28½ ft. dist. mkd. E.M.C. Cor No 2 BT.
A Pine 12" dia., bears S.48°W., 23 ft. dist., mkd. E.M.C. Cor. No 2 BT.

(same surveyor, for Ashley Consolidated Nickel Mines - Survey Nov. 5, 1895 (DCSO records Vol. 28 Page(s) 11846;11847)

Set post 4½ ft. long, 4" sq., 12" in the ground, with mound of stone, mkd. No 2 M.S. 305, set for southwest corner of the consolidated claim; from which
A Pine 24" dia., bears N.28°W., 48 lks. dist., mkd. No. 2 M.S. 305 BT.
A Pine 20" dia., bears N.41½°E., 145 lks. dist., mkd. No. 2 M.S. 305 BT.
Old location post not found, probably destroyed by forest fire.

John H. Markham, Jr. For: Hanna Coal & Ore Co. - Wit: E.D. Jenks; G.D. Myers - Aug/Sept. 1957 - C.S. File 42/288-3

Emerald Lode Claim Corner #2 Sec. 18, as det. by O.B.Ts:
A 30" Pine bears N.28°W., 96.0 ft. found scribe.
A 26" Pine sump (logged) bears N.47½°E., 31.7 ft. O.B.T.
At corner point set brass cap in concrete mkd. E.M.C. #2 T30S R6W 2880 1957 from which
A 15" Cedar bears N.80°W., 45.5 ft. mkd. M.S. 305 #2 BT.
A 22" Fir bears N.82°E., 30.6 ft. mkd. M.S. 305 BT.