

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 910070

PRIMARY CORNER DESCRIPTION Cor. #1 Mineral survey #305

Alias _____ Description Cor. #1 Oregon

Alias _____ Description Cor. #1 Triangle

Alias 918010 Description Cor. #1 MS #186

Alias _____ Description _____

Survey by W.F. Briggs, U.S. Deputy Mineral Surveyor, for Edson Adams & Harvey Brown, Mining Claim Emerald Lode Claim - Survey Nov. 9, 1888 (DCSO records Vol. 28 Page(s) 11839)

Set post, 4 ft. long, 3" sq., 18" in the ground, with a mound of stone alongside, mkd. E.M.C. Cor. No 1; from which

A Fir 6" dia., bears S.56°E., 10 ft. dist., mkd. E.M.C. Cor No 1 BT.

A Pine 4" dia., bears S.30°W., 12 ft. dist., mkd. E.M.C. Cor No 1 BT.

W.F. Briggs, U.S. Deputy Mineral Surveyor under instructions dated Oct. 29, 1895 - Survey Nov. 5, 1895 (DCSO records Vol. 28 Page(s) 11845 and 11846 and 11847)

Beginning at a post 4½ ft. long, 4" square, 12" in the ground with mound of stone, marked No 1 M.S. 305, identical with old location corner set for southeast corner of claim, it also being identical with the northwest corner of the Emerald lode quartz claim for which a patent has been issued to the Oregon Nickel Mining Company. Said post being placed at a point 600 ft. south of quarter post on line between sections 17 and 18, in T.30S R6W, from which

A Fir 8" dia., bears N.33°W., 17 lks. dist., mkd. No 1 M.S. 305 BT.

A Pine 12" dia., bears S.65°W., 67 lks. dist., mkd. No 1 M.S. 305 BT.

John Markham, Jr. for: Hanna Coal and Ore Co. - Wit: G.D. Myers; E.D. Jenks - July/Aug. 1957 - C.S. File 42/288-16

Found - 20" Pine bears S.65°W., 42.4 ft. O.B.T. found scribe.

At corner point, set brass cap in concrete mkd. E.M.C. #1 T30S R6W 2880 1957, from which

A 26" Fir bears N.29°W., 10.5 ft. mkd. M.S. 305 BT.

A 26" Fir bears S.83°E., 19.0 ft. mkd. M.S. 305 BT.

¼ Corner for 17 and 18 bears North 626.0 ft.