

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 100440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 18; & 13 of T30-8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7252)

-----  
Set a Laurel post 3 ft. long, 3" sq., 18" in the ground for the 1/4 sec. cor. marked 1/4 S. on the W. side, from which  
A Fir 11" dia., bears S.44°E., 24 lks. dist. mkd. 1/4 S BT.  
A Laurel 10" dia., bears S.26°W., 23 lks. dist. mkd. 1/4 S BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Dale McFarland; John Powell, crew - June 1962 - C.S. 49/139-93

-----  
Found - Both original BTs as recorded, previously opened, shows good scribing "1/4 S"  
Set brass cap at cor. mkd: County Surveyors Office 1962 R8W 1/4 S13|S18 R7W T30S.  
Both BTs in good condition. We do not scribe new BTs.

BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1350, Surveyed April/May 1987 - (DCSO records Vol. 48 Page(s) 18387-88)

-----  
The 1/4 sec. cor., perpetuated and recorded by Byron in 1962, monumented with an iron post 1 1/4" dia., firmly set, projecting 15" above ground, with brass cap erroneously mkd:

County Surveyors Office  
T 30 S

R R  
7 S 13|S 18 8  
W 1/4 W

1962

from which the remains of the original bearing trees:  
A Fir 26" dia., bears S.44°E., 24 lks. dist. with scribe marks 4 S visible on a previously chopped open blaze.  
A Madrone snag 14" dia., bears S.18°W., 23 1/2 lks. dist., with a rotted blaze. (Rec. S.26°W., 23 lks.)  
and a new bearing tree:  
A Fir 7" dia., bears N.80°W., 6 1/2 lks. dist., mkd. 1/4 S13 BT.

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - Feb. 2, 1990 - C.S. File 64/5-8

-----  
Found - 1962 DCSO 2 1/2" dia. brass cap on a 1 1/4" O.D. Iron pipe, protrudes 14" above ground. Cap is  
(Cont. Next Page)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

erroneously stamped with reverse ranges.

11" now 24" dia. D.Fir with a previously opened blaze scribing visible "4S", bears S.44°E., 15.8 ft. (agrees w/rec) Orig. BT.

10" now 13" dia. Madrone snag, no blazes or marks, is tagged with a yellow BLM tag (15.2 ft. dist. N.26°E., T30S R8W S13, post by C.S. File 7/62). We open tree in two places, no blazes or scribing found. A cat road running NW-SE is along westerly side of tree. This tree has been recorded as an orig. BT in previous records. We have some doubt about it being original, tree bears S.23°W., 15.2 ft.

7" now 7" dia. D.Fir with a partially healed single blaze, scribing visible "¼ S13 BT" bears N.77 3/4°W., 4.6 ft. (Rec. N.80°W., 4.3 ft.) 1987 BLM BT.

Erroneously stamped ranges are stamped out and correct marks are added to brass cap. Cap now reads:

COUNTY SURVEYORS OFFICE  
T 30 S

R		R
8	S13   S18	7
W	¼	W

1962

New BTs -9" dia. D.Fir double blazed and scribed "¼ S13 CS BT" bears N.33°W., 12.0 ft.

7" dia. D.Fir double blazed and scribed "¼ S18 CS BT" bears N.52½°E., 4.4 ft.

Corner lies at the edge of a NE-SW cut line.

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor under Group No. 2139, surveyed July/Aug. 2006 (DCSO records Vol. 57 Page(s) 22537)

-----

The ¼ sec. cor. of secs. 13 and 18, monumented with an iron post, 1¼" dia., firmly set, projecting 12" above ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees

A fir, 27" dia., bears S.44°E., 15.8 ft., with scribe marks 4 S visible on an opened blaze.

A madrone stump, size indeterminate, bears S.18°W., 15.5 ft., with fallen trunk, 14" dia., lying alongside, with no marks visible.

and bearing tree mkd. by Bedell

A fir, 10" dia., bears N.80°W., 4.3 ft., with a healed blaze.

continued next page

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 100440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 18; & 13 of T30-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and bearing trees mkd. by Smith and Flause, in 1990  
A fir, 8" dia., bears N.55¾°E., 4.4 ft., with a healed double blaze.  
A fir, 12" dia., bears N.32¼°W., 11.8 ft., with a healed double blaze.