

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18; & 12 & 13, T30-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7252-53)

Set a Fir post 4 ft. long, 4" sq., 20" in the ground for the cor. to secs. 7, 12, 13 and 18, marked T30S R7W S7 on the NE. face; S18 on the SW. face; and S2 on the NW. face; also with 4 notches on the S. and two notches on the N. angles of same, and from which

- A Fir 14" dia., bears N.56°E., 22 lks. dist. mkd. T30S R7W S7 BT.
- A Fir 14" dia., bears S.56°E., 27 lks. dist. mkd. T30S R7W S18 BT.
- A Fir 10" dia., bears S.65°W., 3 lks. dist. mkd. T30S R8W S13 BT.
- A Pine 18" dia., bears N.47°W., 17 lks. dist. mkd. T30S R8W S12 BT.

Survey by R.H. Gee - For: Roseburg Lumber Co. - March 1955 - C.S. File 41/385-1

Set a 1/2" Iron rod from which bears

- A Fir 26" N.56°E., 14.5 ft. (Old BT)
- A Fir 10" S.75½°W., 25.6 ft. mkd. S13 T30S R8W W.M. (New BT)
- A Fir 14" N.59½°W., 29.0 ft. mkd. S12 T30S R8W. W.M. (New BT)
- A Pine 8" S.25°E., 41.6 ft. mkd. S18 T30S R7W W.M. (New BT)

BLM resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1350, surveyed April/May 1987 - (DCSO records Vol. 48 Page(s) 18388-89)

The sec. cor., perpetuated and recorded by Gee in 1955, monumented with an iron rod, 5/8" dia., firmly set, projecting 16" above ground, from which the remains of original bearing trees:

- A Fir 35" dia., bears N.56°E., 22 lks. dist. with healed blaze.
 - A Fir stump 30" dia., bears S.56°E., 27 lks. dist. no marks remaining.
- and bearing trees mkd. by Gee:
- A Pine 17" dia., bears S.25°E., 63 lks. dist. with healed blaze.
 - A Fir 15" dia., bears S.75½°W., 39 lks. dist. with healed blaze.

(Cont. Next Page)

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18; & 12 & 13, T30-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Fir 20" dia., bears N.59½°W., 44 lks. dist. with healed blaze.

At the corner point

Set an stainless steel post, 28" long, 2 1/2" dia., 22" in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd:

T 30 S
R 8 W R 7 W
S 12 | S 7
S 13 | S 18
1987

from which a new bearing tree:

A Pine 11" dia., bears S.41°E., 39 lks. dist. mkd. T30S

R7W S18 BT.

Deposit white "DEEP-1" magnetic marker at base and iron rod

alongside stainless steel post.

alongside stainless steel post.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 1/22/2025 - C.S. File 67/59-50

Found - BLM brass cap proj 6"
36" Fir N.56°E. 14.5' (rec 22lks) healed blaze.
Very rotted 30" fir stump S.56°E. 17.8' (rec 27lks) no marks.
21" fir S.75½°W. 25.7' (rec 39lks) healed blaze.
25" fir N.59½°W. 29' (rec 44lks) healed single blaze
Very rotted fir stump S.56°E. 17.82' (rec 27lks)
24" pine S.41°E. (rec 39lks) healed double blaze.
Green steel "T" post W. 5' +-

T30S
R8W | R7W
S12 | S7
S13 | S18
1987

OCRS COORDINATE SYSTEM
COTTAGE GROVE-CANYONVILLE ZONE
N 49885.985
E 96734.040
Comp. decl. 14½°