

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 18 and 19

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7280)

-----  
Set a Fir post 3 ft. long, 3" sq., 18" in the ground for ¼ sec. cor. marked ¼ S on N. face, from which  
A Fir 16" dia., bears N.10°E., 46 lks. dist. mkd. ¼ S BT.  
A Cedar 32" dia., bears S.19°E., 45 lks. dist. mkd. ¼ S BT

BLM resurvey by Stephen D. Albright and Jack W. Bowder, Cadastral Surveyors, under Group #787, surveyed July/Aug. 1972 - (DCSO records Vol. 36 Page(s) 14894-95)

-----  
The original ¼ sec. cor., determined at record bearing and distance from the remains of the original bearing trees:

A root hole bears N.10°E., 46 lks. dist. with the rotted remains of a Fir alongside, size indeterminate. No marks remaining.

A Cedar snag 45" dia., bears S.19°E., 45 lks. dist., with scribe mark 4 visible on opened blaze.

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

T 30 S R 7 W  
1/4 S 18  
S 19  
1972

from which new bearing trees:

A Fir 15" dia., bears N.51°W., 23¼ lks. dist. mkd. ¼ S18 BT.

A Fir 7" dia., bears S.17°W., 41 lks. dist. mkd. ¼ S19 BT.

Cor. Fd. and used in BLM resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1350, surveyed April/May 1987 - (DCSO records, Vol. 48 Pg. 18389)