

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7283)

Set a stone 14 x 12 x 6 ins., 10" in the ground for ¼ sec. cor. marked ¼ on N. face, from which
A Laurel 6" dia., bears S.30°W., 22 lks. dist. mkd. ¼ S BT
A Laurel 7" dia., bears N.70°W., 23 lks. dist. mkd. ¼ S BT

BLM resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1350, surveyed April/May 1987 - (DCSO records Vol. 48 Page(s) 18392-93)

The ¼ sec. cor. of secs. 7 and 18, unofficially reestablished by a Bureau of Land Management administrative survey, monumented with an iron pipe, 5/8" dia., firmly set, projecting 14" above ground. There is no remaining evidence of the original corner, therefore, this position is accepted as the corner.

At the corner point

Set an stainless steel post, 28" long, 2 1/2" dia., 26" in the ground, with brass cap mkd:

T 30 S R 7 W
¼ $\frac{S 7}{S 18}$
1987

from which

A Fir 14" dia., bears S.22°W., 36 lks. dist. mkd. ¼ S18 BT

A Fir 15" dia., bears N.80°W., 35 lks. dist. mkd. ¼ S7 BT.

Deposit white "DEEP-1" magnetic marker at base and iron pipe alongside the stainless steel post.

Fd. BC & 2 BTs by D. Edwards, 1/2009 - M158-50