

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 6 and 7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7255)

Set a stone 12 x 12 x 7 ins., 8" in the ground for ¼ sec. cor. marked ¼ on N. face, from which

A Laurel 10" dia., bears N.10°E., 34 lks. dist. mkd. ¼ S BT.

A Laurel 5" dia., bears S.19°E., 21 lks. dist. mkd. ¼ S BT.

BLM resurvey by Wayne L. Rogers; Dale T. Bedell; Boyd W. Peterson, Cadastral Surveyors - under Group #1456, surveyed Sept. 1988/Feb. 1989 - (DCSO records Vol. 50 Page(s) 19036)

The ¼ sec. cor. of secs. 6 and 7, restored by person(s) unknown, monumented with an iron pipe, 3/4 in. diam., firmly set, projecting 20 ins. above ground. This position has long been recognized as the corner by adjacent landowners, and is accepted as the corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 30 S R 7 W

¼ S 6
S 7

1988

from which

A pine, 9 ins. diam., bears S. 66° E., 39 lks. dist., mkd. ¼ S7 BT.

A fir, 15 ins diam., bears N. 24° W., 24 lks. dist., mkd. ¼ S6 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post and 3/4 in. iron pipe alongside.

From this point, a madrone stump, 16 ins. diam., bears N. 59¼° E., 54 lks., dist., with scribe marks BT ¼ visible on opened blaze, facing NW. Records at the office of the Roseburg Lumber Company in Riddle, Oregon, indicate that this tree was marked in 1947 for an unofficial, compass survey point, by company foresters.

Fd. BC & 2 BTs by D. Edwards, 1/2009 - M158-50