

PRIMARY CORNER DESCRIPTION Angle point of So. bdy. Sec. 31

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William H. Byars, Deputy Surveyor, under Contract #448, dated June 13, 1882 - (DCSO records, Vol. 17 Page 7248)

I set at this point, A Laurel post, 4 ft. long, 4" sq., 8" in ground with stone mound 12" high about same. Marked on the NE. side, T30S R7W S32, and T31S R7W S5 on SE.; S6 on SW.; and S31 on the NW. face of same. Also 5 notches on E. and 1 notch on W. angle of same for the cor. to secs. 5, 6, 31 and 43, from which

- A W.Oak 12" dia., bears N.60°E., 8 lks. dist. mkd. T30S R7W S32 BT.
- A Fir 28" dia., bers S.71°E., 29 lks. dist. mkd. T31S R7W S5 BT.
- A Fir 12" dia., bears S.41°W., 30 lks. dist. mkd. T31S R7W S6 BT.
- A W.Oak 8" dia., bears N.33°W., 57 lks. dist. mkd. T30S R7W S31 BT.

GLO resurvey by William H. Byars, Deputy Surveyor under Contract #450, dated July 28, 1882 - (DCSO Records, Vol. 17 Page 7275)

I find that the cor. established for secs. 5, 6, 31 and 32 is in error and is some distwance W. of where the true corner should be. I therefore destroy the witness trees and post common to secs. 5 and 32, marking the same for the W C to secs. 5 and 31. This cor. is therefore marked: T30S R7W on NE.; T31S on SE.; S6 W C on SW. and S31 W C on the NW., and from which

- A Fir 12" dia., bears S.41°W., 30 lks. dist. mkd. T31S R7W S6 W C BT.
- A W.Oak 8" dia., bears N.33°W., 57 lks. dist. mkd. T30S R7W S31 W C BT.

GLO survey by Gerald A. Sorrels, U.S. Surveyor, under Group #36, surveyed March/April 1918 - (DCSO records Vol. 17 Page(s) 7296) and duplicated info. in Vol. 27 Pg. 11618)

Intersect the old cor. of secs. 5 and 6, T31S R7W. located by reference to the old bearing trees., the SE. tree is now dead. At the exact cor. point
Set an iron post 3 ft. long, 1" dia., 26" in the ground, for angle point, with brass cap mkd. AP
1918

from which
(Cont. Next Page)

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 177100

PRIMARY CORNER DESCRIPTION Angle point on So. bdy. Sec. 31

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 18" dia., bears S.37°W., 31 lks. dist. mkd. AP BT
(Old BT)
A Yellow Pine 5" dia., bears N.1°W., 14 lks. dist. mkd. AP
BT (New BT)

Douglas Co. Surveyors Office - Vernon R. Tracy and crew -
June 23, 1965 - C.S. File 53/40-75

Found - 1918 GLO brass cap. AP brass cap is set in rock
mound at foot of overhanging rock bluff approx.
30.0 ft. high.
Orig. 18" now 24" Fir S.37°W., 20.5 ft. shows very
good scar and in good condition.
Orig. 5" now 9" Y.Pine N.1°W., 9.2 ft. shows scribe
on unhealed scar. Tree is now dead due to
porcupine damage.
New BT - 8" D.Fir N.5°E., 12.3 ft. mkd. "AP CS BT", 5 ft. off
ground.
This corner lies approx. 103.0 ft. East of corner for 5 & 6,
T31-7 on South bdy. Sec. 31, T30-7.