

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 31 and 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7273)

Set a Laurel post 3 ft. long, 3" sq., 18" in the ground for 1/4 sec. cor. marked 1/4 S on W. face, from which

A Fir 36" dia., bears S.15°E., 18 lks. dist. mkd. 1/4 S BT.

A Live Oak 12" dia., bears N.58°W., 15 lks. dist. mkd. 1/4 S BT.

GLO survey by Gerald A. Sorrels, U.S. Surveyor, under Group #36, surveyed March/April 1918 - (DCSO records Vol. 17 Page(s) 7302-03) and duplicated info. in Vol. 27 pgs. 11622-23

The old 1/4 sec. cor. located by reference to the bearing trees. At the exact cor. point

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for 1/4 sec. cor., with brass cap mkd:

1/4
S 31 | S 32
1918

from which

A Fir 40" dia., bears S.15°E., 20 lks. dist. mkd. 1/4 S32 BT. (Old BT)

A Live Oak 16" dia., bears N.52°W., 16 lks. dist. mkd. 1/4 S31 BT. (Old BT)

Douglas Co. Surveyors Office - Vernon Tracy, J. Heritage, V. Perron, crew - Nov. 1964 - C.S. File 53/40-96

Found - 1918 GLO brass cap, in place, mkd. "1/4 S31 | S32".

Orig. 40" Fir, now snag, S.15°E., 13.2 ft., scribe visible on log on ground.

Orig. 16" now 14" Live Oak, alive, N.52°W., 10.6 ft., shows scar at base of tree.

New BTs - 8" D.Fir N.18°W., 10.6 ft. mkd. 1/4 S31 CS BT.

6" D.Fir S.46°E., 3.5 ft. mkd. 1/4 S32 CS BT.

This corner lies on westerly edge of top of spur, sloping South.