

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29, 30, 31 and 32

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7276)

Set a stone 18x14x7 ins., 12" in the ground for the cor. to secs. 19, 20, 29 and 30, marked with 2 notches on S. and 5 notches on E. edges, from which

- A Laurel 7" dia., bears N.40°E., 28 lks. dist. mkd. T30S R7W S20 BT.
- A Laurel 12" dia., bears S.63°E., 32 lks. dist. mkd. T30S R7W S29 BT.
- A Fir 16" dia., bears S.50°W., 48 lks. dist. mkd. T30S R7W S30 BT.
- A Fir 48" dia., bears N.33°W., 41 lks. dist. mkd. T30S R7W S19 BT.

BLM resurvey by Stephen D. Albright and Jack W. Bowder, Cadastral Surveyors, under Group #787, surveyed July/Aug. 1972 - (DCSO records Vol. 36 Page(s) 14887)

The Sec. cor., monumented with the original basalt stone, 18 x 14 x 7 ins., loosely set, protruding 15" above the ground, mkd. with 2 grooves on S., and 5 grooves on E. faces, from which the remaining original bearing trees:

- A Madrone 11" dia., bears N.40°E., 28 lks. dist. no marks visible.
- A burned Fir stump 18" dia., bears S.50°W., 48 lks. dist., with axe marks visible on burned blaze.
- A burned Fir snag 25" dia., bears N.33°W., 41 lks. dist. no marks visible.

Set an iron post, 28" long, 2½" dia., 10" in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd:

T 30 S R 7 W
S 19 S 20
S 30 S 29
1972

from which new bearing trees and a bearing object:

- A Fir 12" dia., bears N.6°E., 132 lks. dist., mkd. T30S R7W S20 BT.
- A Fir 33" dia., bears S.4°E., 174 lks. dist. mkd. T30S R7W S29 BT.
- A Sugar Pine 32" dia., bears N.32½°W., 187 lks. dist. mkd. T30S R7W S19 BT.
- A stone, 5 ft. x 4 ft. x 3 ft., bears S.54°W., 36 lks. dist., mkd. X BO on NE. face.

Deposit the stone alongside the iron post.