

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7278)

Set a stone 24 x 14 x 7 ins., 16" in the ground for ¼ sec. cor. mkd. ¼ on W. face, from which
A Cedar 12" dia., bears S.87°E., 24 lks. dist. mkd. ¼ S BT
A Cedar 15" dia., bears S.85°W., 34 lks. dist. mkd. ¼ S BT

Survey by Roger H. Gee - For: Roseburg Lumber Co. - March 11, 1955 - C.S. File 41/385-4

Found an old Cedar BT in sec. 20, scribe marks visible, tree dead and down, stump hole very plain.
Reset corner with 3" x 3" x 40" Cedar post mkd. ¼ S20 on East face and ¼ S19 on West face, from which
A Hemlock 24" N.10½°E., 8.0 ft. mkd. ¼ S20 T30S R7W BT. Tree is tagged.
A Cedar 8" N.83°W., 55.0 ft. mkd. ¼ S19 T30S R7W BT. Tree is tagged.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Jim Halterman crew - Feb. 1964 - C.S. File 53/40-42

Found - All BTs as recorded by Gee.
Note: Corner is in stream, 4 ft. wide, I SET WITNESS CORNER 5 ft. West.
Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 7 W
Wit. Cor. 5 ft. West to
¼ S19 | S20
1964
New BTs -15" Hemlock bears S.5°W., 65 ft. scribed ¼ S19 CS BT WC.
8" Cedar bears N.83°W., 60.0 ft. previously scribed.
24" Hemlock bears N.32°W., 9.4 ft. previously scribed.

BLM resurvey by Stephen D. Albright and Jack W. Bowder, Cadastral Surveyors, under Group #787, surveyed July/Aug. 1972 - (DCSO records Vol. 36 Page(s) 14891)

Corner Report Only
The ¼ sec. cor., perpetuated and recorded by Gee in 1955, from which the remains of the original bearing trees:
A root hole bears S.87°E., 24 lks. dist. with a fallen Cedar 14" dia., alongside, with axe marks visible on opened blaze.
(Cont. Next Page)

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Cedar 14" dia., bears S.85°W., 34 lks. dist. with axe marks visible on opened blaze.
and trees mkd. by Gee in 1955:

A Hemlock 24" dia., bears N.10½°E., 12 lks. dist. with scribe marks ¼ S20 T30S R7W BT visible on open double blaze.

A Cedar 12" dia., bears N.83°W., 84 lks. dist. with scribe marks ¼ S19 T30S R7W BT visible on open double blaze.
The corner point is located in Wildcat Creek, 10 lks. wide; course N.20°W., from S.20°W. in curve.

From the corner point, a witness corner set by Byron in 1964, bears East, 7½ lks. dist. monumented with an iron post, 1" dia., firmly set, protruding 14" above ground, and in a mound of stone, 1½ ft. base, 1 ft. high with brass cap mkd.

	T 30 S	
WIT		COR
5 F		TW
1/4		T0
S 19		S20
		R 7 W
		1964

from which a tree mkd. by Byron in 1964:

A Hemlock 16" dia., bears S.5°W., 99 lks. dist. with illegible scribe marks visible on partially healed double blaze.