

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Pages 7278-79

Set a post 4 ft. long 4" sq., 24" in the ground for the cor. to secs. 17, 18, 19 and 20 marked T30S R7W S17 on NE.; S20 on SE.; S19 on SW.; and S18 on NW. faces with 3 notches on S. and 5 notches on E. edges, from which

- A Fir 38" dia., bears N.14°E., 69 lks. mkd T30S R7W S17 BT
- A Fir 7" dia., bears S.60°E., 12 lks. mkd. T30S R7W S20 BT
- A Fir 8" dia., bears S.38°W., 5 lks. mkd. T30S R7W S19 BT.
- A Fir 34" dia., bears N.30°W., 65 lks mkd. T30S R7W S18 BT

BLM resurvey by Stephen D. Albright and Jack W. Bowder, Cadastral Surveyors, under Group #787, surveyed July/Aug. 1972 - (DCSO records Vol. 36 Page(s) 14892)

Point for the sec. cor., at proportionate distance, falls in a graveled road, 30 lks. wide, bearing North and S.10°W.; there is no remaining evidence of the original corner.

Set an iron post 28" long, 2½" dia., the top 6" below the surface of a graveled road, with brass cap mkd.

T 30 S R 7 W
S 18 | S 17
S 19 | S 20
1972

from which new bearing trees:

- A Fir 10" dia., bears N.42°E., 144 lks mkd T30S R7W S17 BT
- A Fir 10" dia., bears S.06°E., 102 lks mkd T30S R7W S20 BT
- A Fir 19" dia., bears S.45°W., 84½ lks mkd T30S R7W S19 BT
- A Fir 10" dia., bears N.27½°W., 75 lks mkd T30S R7W S18 BT

Cor. Fd. and used in BLM resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1350, surveyed April/May 1987 - (DCSO records, Vol. 48 Pg. 18390)

David Edwards - For: Roseburg Resources - Dec. 2016 - M172-74

Found - Brass Cap

- A 17" dia., fir bears N.42°E., 95.0 ft.
 - A 16" dia., fir bears S.6°E., 65.3 ft.
 - A 26" dia., fir bears S.45°W., 55.8 ft.
 - A 17" dia., fir bears N.27½°W., 49.5 ft.
- All with a healed blaze.

Corner lies on east edge of gravel road, 11" deep.

(Continued to next page.)

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and
Jeff Lorsung - 1/22/2025 - C.S. File 67/59-49

Found - 19" D.Fir N.42°E. 95'
20"x1' sawn fir stump 56°E. 65.3'
32" D.Fir S.45°W. 55.8'
22" D.Fir N.27½°W. 49.5'
All trees have fully healed single blazes.

T30S R7W
S18|S17
S19|S20
1972

OCRS COORDINATE SYSTEM
COTTAGE GROVE-CANYONVILLE ZONE
N 44842.185
E 102176.741

Notes - Corner is on east edge of gravel road.
Comp. decl. 14½°E.