

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7281)

-----  
Set a post 3 ft. long, 3" sq., 18" in the ground for ¼ sec. cor. marked ¼ S. on W. face, from which  
Chinquapin 5" dia., bears S.86°W., 4 lks. dist. mkd. ¼ S BT.  
Laurel 6" dia., bears N.65°E., 12 lks. dist. mkd. ¼ S BT.

BLM resurvey by Stephen D. Albright and Jack W. Bowder, Cadastral Surveyors, under Group #787, surveyed July/Aug. 1972 - (DCSO records Vol. 36 Page(s) 14896)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:  
T 30 S R 7 W  
1/4  
S 18 | S 17  
1972

from which new bearing trees:  
A Chinquapin 8" dia., bears N.84°E., 58½ lks. dist. mkd. ¼ S17 BT.  
A Fir 6" dia., bears S.61°W., 16½ lks. dist. mkd. ¼ S18 BT

Cor. Fd. and used in BLM resurvey by Dale T. Bedell, under Group #1350, surveyed April/May 1987 - (DCSO records, Vol. 48 Page 18391)

David Edwards - For: Roseburg Resources - Dec. 2016 - M172-74

-----  
Found - Brass cap  
A 13" dia., chinquapin bears N.84°E., 38.6 ft.  
A 14" dia., fir bears S.61°W., 10.9 ft.  
Both with healed blaze.  
A six ft steel post is set 2 ft north.