

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7281)

 Set a stone 16x14x12 ins., in a mound of stone, surface being rock, marked with 4 notches on S. and 5 notches on E. faces, from which

- An Oak 8" dia., bears N.63°E., 61 lks. dist. marked T30S R7W S8 BT.
- A Fir 12" dia., bears S.48°E., 78 lks. dist. marked T30S R7W S17 BT.
- A Fir 11" dia., bears S.55°W., 39 lks. dist. marked T30S R7W S18 BT.
- An Oak 12" dia., bears N.34°W., 43 lks. dist. marked T30S R7W S7 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Jim Halterman crew - Feb. 1964 - C.S. File 53/40-43

 Found - All original BTs., except SW. BT. SE. BT, now snag, shows good scribe. NE. BT, shows scribe marks. Corner is in old cat road, earth is excavated to solid rock. Set brass cap at cor. and build mound of rock. Cap mkd:

County Surveyors Office

T 30 S R 7 W

S 7	S 8
S18	S17

1964

- New BTs -Rescribe now 14" W.Oak N.34°W., 28.6 ft. "S7 T30S R7W CS BT"
- 13" R.Fir bears N.18°E., 40.9 ft. scribed "S8 T30S R7W CS BT"
- 10" Cedar bears S.49°E., 45.1 ft. scribed "S17 T30S R7W CS BT"
- 6" R.Fir bears S.37°W., 37.6 ft. scribed "S18 CSBT"

Fd. and used in BLM resurvey by Albright and Bowder, Cadastral Surveyors, under Group #787, surveyed July/Aug. 1972 - (DCSO records, Vol. 36 Page 14897)

BLM resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1350, surveyed April/May 1987 - (DCSO records Vol. 48 Page(s) 18391-92)

 The Sec. cor., monumented with an iron post, 1¼" dia., firmly set, projecting 24" above ground, in a mound of stone, 4 ft. base, 2 ft. high, with brass cap mkd. in 1964 from which the original bearing trees:

(Cont. Next Page)

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

An Oak 16" dia, bears N.63°E., 61 lks. dist., with healed blaze.

An Oak 16" dia., bears N.34°W., 43 lks. dist., with healed blaze.

and the remains of the bearing trees mkd. by Byron in 1964:

A Fir snag 15" dia., bears N.18°E., 62 lks. dist., with scribe marks S8 visible on partially healed blaze.

A root hole bears S.49°E., 69 lks. dist., with a Cedar 12" dia., lying alongside, with scribe marks T30S R7W S17 BT visible on a partially healed blaze.

A Fir 8" dia., bears S.37°W., 57 lks. dist., with healed blaze.

and a new bearing tree:

An Oak 8" dia., bears S.28°E., 209 lks. dist. mkd. T30S R7W S17 BT.

This corner is at latitude 42°58'14.33" N., longitude 123°33'46.40" W. (NAD 1927) and was designated doppler global position station 71008 "OLALLA CREEK", by the Geodetic Control Unit, Bureau of Land Management, Oregon State Office, in 1987.

Fd. BC & 4 BTs by D. Edwards, 1/2009 - M158-50
Fd as per M158-50 by D. Edwards 12/2016 - M172-74