

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5, 6, 7 and 8

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7284)

-----  
Set a Fir post, 4 ft. long, 4" sq., 24" in the ground for the cor. to secs. 5, 6, 7 and 8, marked T30S R7W S5 on NE.; S8 on SE.; S7 on SW.; and S6 on NW. faces, with 5 notches on S. and E. edges, from which

- A Cedar 10" dia., bears N.58°E., 77 lks. dist. mkd. T30S R7W S5 BT.
- A Laurel 14" dia., bears S.28°E., 62 lks. dist. mkd. T30S R7W S8 BT.
- A Laurel 16" dia., bears S.30°W., 74 lks. dist. mkd. T30S R7W S7 BT.
- A Cedar 16" dia., bears N.32°W., 30 lks. dist. mkd. T30S R7W S6 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Jim Halterman crew - Feb. 1964 - C.S. File 53/40-41

-----  
Found - 5/8" Iron rod and steel fence post at corner.  
All original BTs All check record.  
Orig. NE. and SW. BTs show good scribing.  
10" R.Fir bears S.5°E., 33.7 ft. We open and find good scribing. This BT scribed about 8 years ago, probably by Roger Gee.

BLM resurvey by James E. Jelley, under Group # 880, surveyed Aug/Oct. 1975 (DCSO records Vol. 38 Page(s) 15607)

-----  
The sec. cor., perpetuated and recorded by Byron in 1964, monumented with a rebar, 5/8" dia., firmly set, projecting 8" above ground, from which the original bearing trees:

- A Cedar 20" dia., bears N.58°E., 77 lks. dist. with scribe marks 7W visible on open blaze.
- A Madrone 35" dia., bears S.28°E., 62 lks. dist. no marks visible on open double blaze.
- A Cedar 45" dia., bears S.30°W., 74 lks. dist., with scribe marks 7 S visible on partially open blaze.
- A Cedar 45" dia., bears N.32°W., 30 lks. dist., with healed blaze.

and a bearing tree not of record:

- A Fir 15" dia., bears S.5°E., 50 lks. dist., with healed blaze.

At the corner point

(Cont. Next Page)

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5, 6, 7 and 8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground,  
with brass cap mkd:

T 30 S R 7 W  
S 6 | S 5  
S 7 | S 8  
1975

from which a new bearing tree:

A Fir 10" dia., bears S.24½°W., 19½ lks. dist., mkd. T30S  
R7W S7 BT.

Fd. corner as recorded by Jelley in 1975, BLM resurvey by  
Wayne L. Rogers; Dale T. Bedell; Boyd W. Peterson, Cadastral  
Surveyors - under Group #1456, surveyed Sept. 1988/Feb. 1989  
- (DCSO records Vol. 50 Page(s) 19035)

Fd. BC & 4 BTs by D. Edwards, 1/2009 - M158-50  
Fd as per M158-50 by D. Edwards 12/2016 - M172-74

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and  
Jeff Lorsung - 1/28/2025 - C.S. File 67/59-52

Found - 3¼" BLM brass cap (prop mkd) Proj 2".  
20"x2½' broken rotten madrone stump S.28°E. 40.9'E.  
(Rec 62lks)  
27" Cedar N.58°E. 50.8' (Rec 77lks)  
48" Cedar fallen out of position N.32°W. 19.8'  
(Rec 30lks)  
22"x3½' sawn fir stump S.5°E. 33.0' (Rec 50lks)  
13"x16' sawn fir stump S.24½°W. 12.9' (Rec 19½lks)  
Cedar (dia rec 45") S.30°W. 48.8' (Rec 74lks)  
A red steel fence post N.10°W. 5'

Notes - Compass decl. 14¼°E.  
O CRS COORDINATE SYSTEM  
COTTAGE GROVE-CANYONVILLE ZONE  
N. 55293.106 E. 102491.704