

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7287)

Set a stone 16 x 12 x 4 ins., 10" in the ground for 1/4 sec. cor. marked 1/4 on W. face, from which

A Fir 24" dia., bears N.16°W., 14 lks. dist. mkd. 1/4 S BT.

A Laurel 5" dia., bears S.24°E., 50 lks. dist. mkd. 1/4 S BT

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Jim Halterman crew - Feb. 1964 - C.S. File 53/40-40

Found - 5/8" Iron rod at corner.

Orig. 24" now 38" R.Fir N.16°W., 9.2 ft., find good bark scribing, near base.

Orig. SE. BT not found.

Corner stone not found.

Corner is on East slope and about 100 ft. South of small stream.

Set Brass cap at cor. mkd: County Surveyors Office

T 30 S R 7 W

1/4 S6 | S5

1964

Rescribed now 38" R.Fir N.16°W., 10.2 ft. "1/4 S6 CS BT"

New BT - 24" R.Fir bears N.58°E., 23.6 ft. scribed "1/4 S5 CSBT"

BLM resurvey by Wayne L. Rogers; Dale T. Bedell; Boyd W. Peterson, Cadastral Surveyors - under Group #1456, surveyed Sept. 1988/Feb. 1989 - (DCSO records Vol. 50 Page(s) 19038)

The 1/4 sec. cor. of secs. 5 and 6, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1964, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S

S 6 | S 5

1/4

R 7 W

1964

from which the remains of an original bearing tree

A fir snag, 38 ins. diam., bears N. 16° W., 14 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

and the remains of a bearing tree mkd. by Byron

A fir snag, 24 ins. diam., bears N. 55 ° E., 156 lks. dist., with healed blaze.

(Cont. Next Page)

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

and new bearing trees

A cedar, 6 ins. diam., bears S. 79½° E., 47 lks. dist.,
mkd. ¼ S5 BT.

A cedar, 5 ins. diam., bears S. 11° W., 30 lks. dist.,
mkd. X BT.

Ken Hoffine - For: Lone Rock Timberland Co - 9/2015 - M169-79

Found - 1964 County cap properly marked 1 ft above ground
38" fir snag bears N.17½°W., 10.35 ft (rec. N.16°W.,
9.24 ft) healed face and we retag

11" cedar bears S.79°E., 30.9 ft (rec. S.79½°E.,
31.02 ft) healed face and we retag

9" cedar bears S.11°W., 19.1 ft (rec. S.11°W., 19.8
ft) healed face and tag

New - 9" D.Fir bears S.80¾°W. 20.4 ft we scribe ¼ S6 BT
and tag tree.

Corner lies on extremely steep northeast slope and is approx.
100 feet south of small draw.