

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7277)

Set a Fir post 3 ft. long, 3" sq., 18" in the ground for ¼ sec. cor. marked ¼ S on N. face, from which

A Live Oak 4" dia., bears N.10°E., 29 lks. dist. mkd. ¼ S BT.

A Laurel 7" dia., bears S.9°W., 61 lks. dist. mkd. ¼ S BT.

BLM resurvey by Stephen D. Albright and Jack W. Bowder, Cadastral Surveyors, under Group #787, surveyed July/Aug. 1972 - (DCSO records Vol. 36 Page(s) 14888-89)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 30 S R 7 W

1/4 $\frac{S\ 20}{S\ 29}$

1972

from which new bearing trees:

A Fir 10" dia., bears N.73°E., 38 lks. dist. mkd. ¼ S20 BT.

A Fir 12" dia., bears S.18°W., 27 lks. dist., mkd. ¼ S29 BT.