

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 20

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7279)

Set a Fir post 3 ft. long, 3" sq., 18" in the ground, for the 1/4 sec. cor. marked 1/4 S on N. face, from which
A Pine 38" dia., bears N.31°E., 34 lks. dist., mkd. 1/4 BT
A Fir 24" dia., bears S.22°E., 76 lks. dist. mkd. 1/4 S BT.

BLM resurvey by Stephen D. Albright and Jack W. Bowder, Cadastral Surveyors, under Group #787, surveyed July/Aug. 1972 - (DCSO records Vol. 36 Page(s) 14893)

Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:
T 30 S R 7 W
1/4 $\frac{S\ 17}{S\ 20}$
1972

from which new bearing trees:
A Fir 7" dia., bears N.65 1/2°W., 104 lks. dist. mkd. 1/4 S17 BT.
A Fir 34" dia., bears S.29°E., 46 lks. dist. mkd. 1/4 S20 BT. This tree previously mkd. by person(s) unknown with scribe marks 1/4S BT visible on bark blaze.