

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7282)

Set a pine post 3 ft. long 3" sq. 18" in the ground for ¼ sec. cor. mkd ¼ S on N face from which
 A pine, 32" dia., bears N.54°W., 24 lks., mkd: ¼ S BT.
 A pine, 16" dia., bears S.69°W., 58 lks., mkd: ¼ S BT.

David Edwards - For: Roseburg Resources - Dec. 2016 - M172-74

At proportionate position
Set - 5/8"x30" steel rebar with 2½" dia., alum. cap mkd pas per the 2009 BLM manual and "ROSEBURG RESOURCES CO" and "LS 2339" and "2016" set.
 A 6" dia. fir bears S.24°E., 10.8 ft.
 A 7" dia., fir bears N.54°W., 8.5 ft.
 6 ft. steel posts are set 2 ft East & 2 ft West.