TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 8

Alias Description
Alias Description
Alias Description
Alias Description

GLO survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7285)

Set a stone 14 x 12 x 5 ins., 10" in the ground for ¼ sec. cor. marked ¼ on N. face, from which
A Pine 12" dia., bears S.8°W., 52 lks. dist. mkd. ¼ S BT.
An Oak 15" dia., bears N.66°W., 218 lks. dist. mkd. ¼ S BT

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #880, surveyed Aug/Oct. 1975 - (DCSO records Vol. 38 Page(s) 15606-07)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

¼ S 5 / S 8

T 30 S R 7 W
1975

from which
A Fir 10" dia., bears N.18¼°W., 59 lks. dist. mkd. ¼ S5 BT.
A Fir 7" dia., bears South, 29½ lks. dist. mkd. ¼ S8 BT.

Ken Hoffine - For: Lone Rock Timberland Co - 9/2015 - M169-79

Found - 1975 BLM cap properly marked 0.3 ft above ground.
24" D.Fir bears N.18½°W., 38.25 ft (rec. N.18¼°W., 38.94 ft) healed face and tag.
22" D.Fir bears S.2¾°W., 19.1 ft (rec South 19.47 ft) healed face and tag.
Corner lies on gentle ground and is in the middle of narrow band of timber with brushy open areas to the east and west.

Fd as per M169-79, Set 6 ft steel post 2 ft west, by D. Edwards 12/2016 - M172-74