

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 276100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4 & 5 only, T31-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 17 Page(s) 7230)

-----  
Set a post on offset line (10 chs. South of line) as corner to secs. 4, 5, 32 and 33, from which  
A B.Oak 5" dia., bears S.60°E., 10 lks. dist.  
A B.Oak 5" dia., bears S.15°W., 10 lks. dist.  
No trees to the North. Made rock mound.

GLO survey by Gerald A. Sorrels, U.S. Surveyor, under Group #36, surveyed March/April 1918 - (DCSO records Vol. 17 Page(s) 7294 and Vol. 19 Pgs. 8092-93) and (duplicated pgs. 11616 and 11638)

-----  
(Pg. 7294)  
(S.88°18'W., 3.88 chs. from Sec. cor. for 32 & 33, T30-7)  
Point for cor. of secs. 4 & 5, falls on conglomerate bluffs where it is impracticable to establish cor.

(Pgs. 8092-93)  
70.00 chs. After diligent search, I fail to find any evidence of the old witness cor.

77.75 chs. Foot of conglomerate bluffs.  
Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for witness cor. to the cor. of secs. 4 and 5, with brass cap mkd.

WC  
-----  
S5 | S4  
T31S | R7W  
1918

from which  
A Live Oak 6" dia., bears S.87°30'W., 51 lks. dist. mkd.  
W C T31S R7W S5 BT.

A W.Oak 10" dia., bears S.55°15'E., 126 lks. dist. mkd. W  
C T31S R7W S4 BT.

78.08 chs.  
Intersect the N. bdy. of the Tp.

Fd. OK, Sept. 1984 by H. Johnstone - M 97-50  
Fd. OK by Kris DeGroot - July 2007 - M153-58