

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7262)

Set a Fir post 4 ft. long, 4" sq., 24" in the ground for the cor. to secs. 28, 29, 32 and 33, marked T30S R7W S28 on NE.; S33 on SE.; S32 on SW.; and S29 on NW. faces, with 1 notch on S. and 4 notches on E. edges, from which

- A Fir 13" dia., bears N.63°E., 55 lks. dist. mkd. T30S R7W S28 BT.
- A Fir 18" dia., bears S.70°E., 24 lks. dist. mkd. T30S R7W S33 BT.
- A Laurel 15" dia., bears S.56°W., 48 lks. dist., mkd. T30S R7W S32 BT.
- A Laurel 14" dia., bears N.13°W., 27 lks. dist. mkd. T30S R7W S29 BT.

GL0 survey by Gerald A. Sorrels, U.S. Surveyor, under Group #36, surveyed March/April 1918 - (DCSO records Vol. 17 Page(s) 7300-01) and duplicated info. in Vol. 27 Pg. 11621)

The old cor. of secs. 28, 29, 32 and 33, located by reference to the bearing trees. The NW. tree has fallen. At the exact corner point

Set an iron post 3 ft. long, 2" dia., 24" in the ground, for sec. cor., with brass cap marked:

T30S	R7W
S29	S28
S32	S33
1918	

from which

- A Fir 18" dia., bears N.59°E., 58 lks. dist. mkd. T30S R7W S28 BT. (Old BT)
- A Fir 30" dia., bears S.80°E., 24 lks. dist. mkd. T30S R7W S33 BT. (Old BT)
- A Madrone 20" dia., bears S.62°W., 45 lks. dist. mkd. T30S R7W S32 BT. (Old BT)
- A Fir 30" dia., bears N.7°W., 58 lks. dist. mkd. T30S R7W S29 BT. (New BT)

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V. Perron, crew - Nov. 12, 1969 - C.S. 53/40-97

Found - 1918 GL0 brass cap, in place and properly marked.
Orig. 30" now 40" W.Fir, alive, S.80°E., 15.8 ft., shows good scar, we tag.
Remains of 30" Fir N.7°W., 38.3 ft., down, badly decayed, scribe on unhealed blaze.
No trace of other original bearing trees.

(Cont. Next Page)

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs -8" W.Fir S.47°W., 75.3 ft. mkd. T30S R7W S32 CS BT.
14" W.Fir N.80°W., 65.8 ft. mkd. T30S R7W S29 CS BT.
8" W.Fir N.21°E., 54.3 ft. mkd. T30S R7W S28 CS BT.
This corner lies on SE. slope about 200 ft. N. of logging
access road.

Fd OK, Sept. 1984 by H. Johnstone - M 97-50