

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7263)

Set a sandstone 12 x 12 x 10 ins., 8" in the ground for ¼ sec. cor. marked ¼ on W. face, from which

A Laurel 10" dia., bears N.70°E., 22 lks. dist. mkd. ¼ S BT.

A Laurel 7" dia., bears S.59°W., 19 lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Mike Darby, Terry Connell, crew - July 1965 - C.S. File 53/40-83

Found - Stone 12x11x5", badly chipped, no marks. Recorded to be 12x12x10".

Orig. 10" now 11" laurel N.70°E., 14.5 ft. turned out and dead, upper scar badly rotted, lower scar healed over. Open and find "BT" and axe notch.

Only a hole where other BT should have been.

Set Brass cap at cor. mkd: County Surveyors Office

T 30 S R 7 W

¼ S28 | S29

1965

New BTs -6" Hemlock N.22°E., 5.5 ft. mkd. ¼ S28 CS BT.

14" D.Fir N.68°W., 17.0 ft. mkd. ¼ S29 CS BT.

Corner lies 50.0 ft. West of top of bluff 75.0 ft. high.