

PRIMARY CORNER DESCRIPTION Sec Cor for 20, 21, 28 and 29

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7264)

-----  
Set a Fir post 4 ft. long, 4" sq., 24" in the ground for the cor. to secs. 20, 21, 28 and 29 marked T30S R7W S21 on NE.; S28 on SE.; S29 on SW.; and S20 on NW. faces, with 2 notches on S. and 4 notches on E. edges, from which  
A Laurel 14" dia. bears N.22°E. 61 lks mkd T30S R7W S21 BT  
A Laurel 14" dia. bears S.42°E. 58 lks mkd T30S R7W S28 BT  
A Cedar 14" dia. bears S.40°W., 50 lks mkd T30S R7W S29 BT  
A Fir 26" dia., bears N.69°W., 34 lks. mkd T30S R7W S20 BT

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Mike Darby, J. Barnett, crew - May 21, 1965 - C.S. File 53/40-69

-----  
Found - Orig. 14" now 17" Laurel S.42°E., 38.3 ft., shows scar, did not open.  
Orig. 14" now 22" Cedar S.40°W., 33.0 ft., now dead snag. Previously opened, log in front prevents seeing into opening.  
Orig. 26" now 38" Fir N.69°W., 22.4 ft., shows scribing.

Set Brass cap at cor. mkd: County Surveyors Office  
T 30 S R 7 W  
S 20 | S 21  
S 29 | S 28  
1965

New BTs -22" D.Fir S.3°E., 11.7 ft. mkd. T30S R7W S28 CSBT.  
7" D.Fir N.23°E., 5.9 ft. mkd. T30S R7W S21 CSBT.  
11" D.Fir N.45°W., 41.5 ft. mkd. T30S R7W S29 CSBT  
26" D.Fir S.81°W., 26.9 ft. mkd. T30S R7W S29 CSBT  
This corner lies 27.0 ft. East of creek, flowing S.20°E.

Cor. Fd. and used in BLM resurvey by Albright and Bowder, Cadastral Surveyors, under Group #787, surveyed July/Aug. 1972 - (DCSO records, Vol. 36 Pg. 14888)

Fd. OK, April 1993 by M. Smalley - C.S. File 63/153-8

Greg Lang - June 2013 - C.S. File 65/78-52

-----  
Found Brass Cap set in 1965  
Found - now 40" Fir (record N.69°W., 22.4' to face) Note: I set a spike at 23.70' in center and side of tree.  
now 16" D.Fir (record N.45°W., 41.50)  
Also fd a stump to the SE, a snag to the NE, and a stump to the SW per the 1965 renewal.

continued next page

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Sec Cor for 20, 21, 28 and 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- 9" D.Fir bears N.12½°E., 27.80' scribed "S21 BT"  
6" D.Fir bears S.14¼°E., 9.70' scribed "S28 BT"  
Note - Bearings are to the center of the trees and  
distances are measured to a spike in side of the  
trees.  
Corner lies approx. 30 ft East of a small creek.