

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 21

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7265)

-----  
Set a Fir post 3 ft. long, 3" sq., 18" in the ground for ¼ sec. cor. marked ¼ S. on W. face, from which  
A Fir 10" dia., bears S.80°W., 14 lks. dist. mkd. ¼ S BT  
A Laurel 12" dia., bears S.15°E., 15 lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, M. Darby, J. Barnett, crew - April/May 1965 - C.S. File 53/40-70

-----  
Found - Orig. 10" now 24" Fir, S.80°W., 9.2 ft., open, shows "4 S".

No trace of Laurel BT.

Set Brass cap at cor. mkd: County Surveyors Office

T 30 S R 7 W  
¼ S20 | S21  
1965

New BTs -14" Cedar N.49°E., 14.7 ft. mkd. ¼ S21 CS BT.

11" D.Fir N.54°W., 16.5 ft. mkd. ¼ S20 CS BT.

This corner lies approx. 100.0 ft. E. of foot of bluffs 65 ft. high, running N. and S.

Fd. and used in BLM survey by Lance Bishop, Cadastral Surveyor, under Group #1170, surveyed Sept. 1983 - (DCSO Records, Vol. 47 Pages 17841-42)

Greg Lang - June 2013 - C.S. File 65/78-53

-----  
Found - Brass cap set in 1965.

now 22" Cedar bears N.48½°E., 14.70'

now 17" D.Fir bears N.55¾°W., 16.50'

New BTs- 12" I.Cedar bears S.57¼°E. 31.80' scribed "¼ S21 BT"

19" I.Cedar bears S.55¼°W. 21.30' scribed "¼ S20 BT"

Note - Bearings are to the center of the trees & distances are measured to a spike in side of the trees.

Corner lies East of a rock Bluff.