

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7267)

A Fir tree, 4" dia., which I marked 1/4 S on W. face for 1/4 sec. cor. and from which
 A Fir 4" dia., bears S.46°W., 6 lks. dist., mkd. 1/4 S BT.
 A Fir 6" dia., bears S.60°E., 14 lks. dist. mkd. 1/4 S BT.

Survey by Howard W. Johnstone - For: Roseburg Lumber Co. - Wit: Henrickson and Clark - Sept. 4, 1963 - C.S. File 51/163-10

Found - Orig. corner tree, now 12" dia., D.Fir.
 6" D.Fir S.60°E., 9.2 ft., now 16" dia.
Scribed -12" D.Fir S.44½°E., 23.5 ft.

Cor. searched for, not found - DCSO, V.Tracy - July 31, 1973 - C.S. File 56/35-5

Douglas Co. Surveyors Office - L.E. Monrean, Deputy - Peter Earle, crew - Oct. 24,, 1973 - C.S. File 56/39-10

Found - Orig. corner tree, now 14" dia., with blaze to West.
 12" D.Fir stump 4 ft. high scribed "1/4S", S.58°W., (Rec. S.46°W.) 4.8 ft., center to center.
 16" now 20" Fir, S.60°E., 9.6 ft., shows faint blaze
 12" now 12" Fir, bears S.44½°W., 23.5 ft.
Set brass cap S.40°E., 1.5 ft. from center of corner tree, marked: County Surveyors Office
 T 30 S R 7 W
 1/4
 S 17 | S 16
 1973