

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7268)

-----  
Set a stone 15 x 14 x 6 ins., 10" in the ground for the cor. to secs. 8, 9, 16 and 17, marked with 4 notches on S. and E. edges, from which

- A Fir 20" dia., bears N.71°E., 72 lks. dist. mkd. T30S R7W S9 BT.
- A Fir 22" dia., bears S.15°E., 7 lks. dist. mkd. T30S R7W S16 BT.
- A Laurel 7" dia., bears S.54°W., 53 lks. dist. mkd. T30S R7W S17 BT.
- A Fir 20" dia., bears N.18°W., 60 lks. dist. mkd. T30S R7W S8 BT.

Douglas County Surveyors Office - Vernon R. Tracy; Mike Darby, crew - May/June 1965 - C.S. File 53/40-72

-----  
 Found - Rock as called for broken in several pieces with 4 notches on the largest piece.  
 Orig. 20" now 38" Fir N.71°E., 47.5 ft., shows "T3S R W 9 BT" in poor bark scribe.  
 Orig. 22" now 39" Fir S.15°E., 4.6 ft., shows 'T30S R7W S16 BT" in bark scribe, good condition.  
 Orig. 20" now 38" Fir stump N.18°W., 39.6 ft., burned, shows no scar, old axe mark in bark.

Set Brass cap at cor. mkd: County Surveyors Office

T	30	S	R	7	W
	S	8		S	9
	S	17		S	16
					1965

Brass cap set in mound of stone.  
New BT - 14" Laurel S.79°W., 24.4 ft. mkd. T30S R7W S17 CSBT.  
No other trees available as corner falls in logged off area.

Cor. Fd. and used in BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #880, surveyed Aug/Oct. 1975 - (DCSO records, Vol. 38 Pages 15602-03)

BLM retracement by A. Bert Skeesick, Cadastral Surveyor, under Group No. 2300, surveyed June/July 2006 - (DCSO records: Vol. 56 Page(s) 22288 and BLM Plat T30-7 2011)

-----  
The cor. of secs. 8, 9, 16 and 17, remonumented by Tracy, in 1965, monumented with an iron post, 1¼" dia., firmly set, projecting 2" above ground, with brass cap (properly) mkd. from which the remains of the original BTs

continued next page

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A fir snag, 41" dia., bears N.71°E., 47.5 ft., with no marks visible.  
A fir snag, 47" dia., bears S.15°E., 4.6 ft., with fragmentary scribe marks visible on a bark blaze.  
A sawed, decayed fir stump, 32" dia., bears N.18°W., 39.6 ft., with no marks visible.  
and remains of a BT mkd. by Tracy, reported by Jelley  
A roothole bears S.79°W., 24.4 ft., with fallen madrone trunk lying alongside, with fragmentary scribe marks visible on a partially healed blaze.  
and new bearing trees  
A fir, 6" dia. bears N.15¼°E., 12.7 ft mkd. T30S R7W S9 BT  
An oak, 7" dia., bears S.66½°E.. 24.4 ft., mkd. T30S R7W S16 BT.  
A fir, 15" dia., bears S.84°W., 24.1 ft., mkd. T30S R7W S17 BT.  
A pine, 7" dia., bears N.31¼°W., 26.2 ft., mkd. T30S R7W S8 BT.  
Latitude 42°58'14.1" N. Longitude 123°32'39.9" W.  
(NAD 1983)

Fd as per 2011 BLM resurvey by D. Edwards, Set 6 ft. steel post 2 ft west. - 12/2016 - M172-74