

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7269)

Set a Maple post, 3 ft. long, 3" sq., 18" in the ground, for 1/4 sec. cor. marked 1/4 S on W. face, from which
An Alder 8" dia., bears N.49°W., 40 lks. dist. mkd. 1/4 S BT
A Fir 18" dia., bears S.85°E., 11 lks. dist. mkd. 1/4 S BT.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #880, surveyed Aug/Oct. 1975 - (DCSO records Vol. 38 Page(s) 15603)

Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

1/4
S 8 | S 9
T 30 S R 7 W
1975

from which

A Fir 5" dia., bears S.32°E., 77 1/2 lks. dist. mkd. 1/4 S9 BT.

A Fir 5" dia., bears S.74 1/2°W., 60 lks. dist. mkd. 1/4 S8 BT.

Used on a BLM retracement by A. Bert Skeesick, Cadastral Surveyor, under Group No. 2300, surveyed June/July 2006 - (DCSO records: Vol. 56 Page(s) 22288 and BLM Plat T30-7 2011)

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2300, Surveyed March/April 2010 - (DCSO records BLM Plat 2011-2 & Vol. 57 Page(s) 22688)

The 1/4 sec. cor. of secs. 8 and 9, monumented with on iron post, 2 1/2" dia., projecting 4" above ground, with a brass cap (properly) mkd.

from which bearing trees mkd. by Jelley in 1975

A fir, 23" dia., bears S.32°E., 51.2 ft.. with a healed blaze.

A fir. 18" dia., bears S.74 1/2°W., 39.6 ft., with a healed blaze.

Fd as per 2011 BLM resurvey by D. Edwards 12/2016 - M172-74