

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7270)

-----  
Set a stone 14 x 10 x 6 ins., 9" in the ground for cor. to secs. 5, 6, 8 and 9 marked with 5 notches on S. and 4 notches on E. edges, from which

A Maple 12" dia., bears N.50°E., 22 lks. dist. mkd. T30S R7W S9 BT.

A Laurel 22" dia., bears S.30°E., 31 lks. dist. mkd. T30S R7W S9 BT.

A Laurel 7" dia., bears S.10°W., 39 lks. dist. mkd. T30S R7W S8 BT.

A Fir 14" dia., bears N.79°W., 23 lks. dist. mkd. T30S R7W S5 BT.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #880, surveyed Aug/Oct. 1975 - (DCSO records Vol. 38 Page(s) 15604)

-----  
The sec. cor., determined at record bearing and distance from the remains of the original bearing trees:

A Madron 35" dia., bears S.30°E., 31 lks. dist., with axe marks visible on decayed double blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 30 S R 7 W  
S 5 | S 4  
S 8 | S 9  
1975

from which new bearing trees:

A Fir 6" dia., bears N.83 3/4°E., 44½ lks. dist. mkd. T30S R7W S4 BT.

A Fir 5" dia., bears S.81¼°E., 31 lks. dist. mkd. T30S R7W S9 BT.

A Fir 5" dia., bears S.81¼°W., 33 lks. dist. mkd. T30S R7W S8 BT.

A Fir 6" dia., bears N.53 3/4°W., 29 lks. dist. mkd. T30S R7W S5 BT.

Corner is further substantiated by old N., S., and W. blazed line. Blazed line going N. from corner has been dated by ring count to approx. 1892. The S. and W. blazed lines look very old but are bark blazed.

Survey by Howard W. Johnstone - For: Roseburg Lumber Co. - June 29, 1984 - M 97-14

-----  
(Cont. Next Page)

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

CORNER REPORT ONLY

Found - 1975 Cadastral brass cap.  
8" Fir N.51°W., (N.53 3/4°W.) 19.1 ft., healed.  
6" Fir N.80°W., (S.81¼°W.) 21.9 ft., scribe visible.  
9" Fir N.76°E., (N.83 3/4°E.) 29.4 ft., healed.  
8" Fir S.84°E., (S.81¼°E.) 20.5 ft., healed.  
(Compass declination 21° East.)

Ken Hoffine - For: Lone Rock Timberland Co - 9/2015 - M169-79  
-----

Found - 1975 BLM cap properly marked 0.2 ft above ground.  
23" D.Fir bears N.50½°W., 19.2 ft (rec. N.51°W.,  
19.1 ft) healed face and tag.  
16" D.Fir bears N.79½°.,W 21.5 ft (rec. N.80°W.,  
21.9 ft) healed face and tag.  
18" D.Fir bears N.75½°E., 28.7 ft (rec. N.76°E.,  
29.4 ft) healed face and tag.  
16" D.Fir bears S.83½°E., 20.5 ft (rec. S.84°E.,  
20.5 ft) healed face and tag.  
Corner lies on steep north facing slope in extremely rocky  
soil.