

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7271)

Set a Pine post 3 ft. long, 3" sq., 18" in the ground for the 1/4 sec. cor. marked 1/4 S on W. face, from which
An Oak 12" dia., bears S.45°E., 19 lks. dist. mkd. 1/4 S BT.
An Oak 6" dia., bears West, 73 lks. dist. mkd. 1/4 S BT.

Survey by Wm. Briggs - Sept. 13, 1897 - Field Book 2 Page 20

Rock monument.
Fir 12" dia., bears S.31 1/2°W., 37 lks.
Cedar 4" dia., bears N.70°E., 29 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Jim Halterman crew - Feb. 1964 - C.S. File 53/40-50

Found - No original BTs. Do find rock mound at corner.
12" now 24" R.Fir S.31 1/2°W., 24.4 ft., we open and find good scribing.
NE. BT, not found. (Briggs)

Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 7 W
1/4 S5 | S4
1964

New BTs -12" R.Fir bears N.23°W., 9.5 ft. scribed 1/4 S5 CSBT.
12" R.Fir bears S.37°E., 26.7 ft. scribed 1/4 S4 CSBT

Corner Fd. and used in BLM survey by James E. Jelley, under Group #880, surveyed Aug/Oct. 1975 - (DCSO Records, Vol. 38 Pg. 15606)

Fd. OK, June 1984 by Howard Johnstone - M 97-14

Ken Hoffine - For: Lone Rock Timberland Co - 9/2015 - M169-79

Found - 1964 County cap properly marked 0.3 ft above ground.
16" D.Fir bears N.24 1/2°W., 9.1 ft (rec. N.23°W., 9.5 ft) healed face and tag.
20" D.Fir bears S.37 1/4°E., 26.9 ft (rec. S.37°E., 26.7 ft) healed face and tag.
Corner lies on gently sloping open oak covered ground.