

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7262)

Set a Laurel post 3 ft. long, 3" sq., 18" in the ground for 1/4 sec. cor. marked 1/4 S on N. face, from which
A Pine 18" dia., bears S.11°E., 39 lks. dist. mkd. 1/4 S BT.
A Cedar 30" dia., bears S.84°W., 67 lks. dist. mkd. S BT.

GLO survey by Gerald A. Sorrels, U.S. Surveyor, under Group #36, surveyed March/April 1918 - (DCSO records Vol. 17 Page(s) 7300) and duplicated info. in Vol. 27 Pg. 11621)

The point for old 1/4 sec. cor. located by reference to the bearing trees. The SE. tree has fallen. At the exact cor. point, Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for 1/4 sec. cor, with brass cap mkd. 1/4 S28
S33
1918

from which
A Yellow Pine 30" dia., bears S.2°W., 66 lks. dist. mkd. 1/4 S33 BT. (New BT)
A Cedar 48" dia., bears N.83°W., 68 lks. dist. mkd. 1/4 S28 BT. (Old BT)

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V. Perron, crew - Nov. 12, 1969 - C.S. 53/40-100

Found - 1918 GLO brass cap, in place and properly marked. Orig. 48" now 54" Cedar, alive, N.83°W., 44.9 ft. "1/4 S BT" bark scribe, poor and "1/4 S28 BT" on unhealed blaze.
1918 Pine, now burned snag, no scribe found.
New BTs - 12" D.Fir N.9°E., 13.3 ft. mkd. 1/4 S28 CS BT.
5" Cedar S.81°E., 14.9 ft. mkd. 1/4 S33 CS BT.
This corner lies in thicket of Laurel, young Fir and Pine.

Mark Smalley - For: Roseburg Resources Co. - January 2000 - M 134-7

Found - GLO brass cap on iron pipe
47" (54") Cedar N.83°W., 4.9 ft. healed orig.
9" Cedar S.81°E., 14.9 ft. healed.
13" Fir N.9°E., 13.3 ft. healed.
(30) Pine S.2°W., 44.0 ft. (43.6') pitch core with double blazes showing no scribed.
New BT - 10" Fir S.57°E., 54.4 ft. "1/4 S BT"

continued next page

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ron Quimby - Crew: R. Olsen & J. Leonard - 9/2017 - C.S. File 65/99-5

Found - 1918 GLO brass cap on 1" Iron pipe (properly mkd)
48" cedar N.83°W., 4.9 ft. good scar.
12" cedar S.81°E., 14.9 ft. good scar. (snag)
16" fir N.9°E., 13.3 ft. good scar.
12" fir S.57°E., 54.4 ft. good scar.
Burnt root hole S.2°W, 44.0 ft.
New - 14" Fir N.84°E., 27.0 ft. scribed ¼ S28 BT.
Note - Area badly burnt 8/2017
Dec. 15½°E