

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 16

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #450, dated July 28, 1882, - (DCSO records Vol. 17 Page(s) 7269)

-----  
Set a Fir post, 3 ft. long, 3" sq. 18" in the ground for 1/4 sec. cor. mkd. 1/4 S on N. face, from which  
A Fir 15" dia., bears N.52°E., 36 lks. dist. mkd. 1/4 S BT.  
A Fir 15" dia., bears S.52°W., 58 lks. dist. mkd. 1/4 S BT.

Douglas County Surveyors Office - James W. Byron, Deputy - Milo Godfrey; Clete Putnam - April 1, 1960 - C.S. File 52/22

-----  
Found - Orig. 15" now 36" Fir, shows good bark scribing "1/4S", N.52°E., 23.8 ft.  
Orig. 15" now 34" Fir S.25°W., (Rec. S.52°W., 38.3 ft.) shows good bark scribing "1/4S".

Note: 1/4 Cor. is in roadway of proposed road.

Set a WITNESS CORNER.

Set brass cap 80 ft. West of corner mkd. County Surveyors  
Office  
Wit. Cor. 80'E to  
1/4 S 9 T30S  
S16 R7W  
1960

New BTs -40" Cedar bears S.43°W., 11.5 ft. scribed WC 1/4 S16  
CS BT.  
34" R.Fir bears S.48°E., 12.3 ft. scribed WC 1/4 S16  
CS BT.

DCSO, VRT - 7/18/1973 - C.S. 56/34-18 - (Wit Cor.) 1960 BC & BTs OK