

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7270)

Set a Laurel Post 3 ft. long, 3" sq., 18" in the ground for 1/4 sec. cor., marked 1/4 S on N. face, from which

A Fir 46" dia., bears South 18 lks. dist. mkd. 1/4 S BT.

A Laurel 6" dia., bears N.54°E., 30 lks. dist. mkd. 1/4 S BT

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #880, surveyed Aug/Oct. 1975 - (DCSO records Vol. 38 Page(s) 15605)

Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

1/4 $\frac{S\ 4}{S\ 9}$

T 30 S R 7 W
1975

from which

A Fir 7" dia., bears N.31°E., 11 lks. dist. mkd. 1/4 S4 BT.

A Fir 22" dia., bears S.21°W., 31 1/2 lks. dist. mkd. 1/4 S9 BT.