

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 360300

PRIMARY CORNER DESCRIPTION East 1/16 cor. betw. 21 and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by John Jelley, Cadastral Surveyor, Group #571, surveyed May/June 1965 - (DCSO records Vol. 33 Page(s) 13869-70)

Point for the WITNESS corner to the E 1/16 sec. cor. of secs. 21 and 28.

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.
$$\begin{array}{r} \text{E } 1/16 \quad \frac{\text{S } 21}{\text{S } 28} \quad \text{WC} \rightarrow \\ 1965 \end{array}$$

from which

A W. Fir 20" dia., bears N.79°E., 47 lks. dist. mkd. X BT.

A W. Fir 12" dia., bears S.20°E., 31 lks. dist. mkd. X BT.

Corner report by Douglas Co. Surveyors Office - V.R. Tracy and crew - Nov. 12, 1969 - C.S. File 53/40

Wit. Cor. set in 1965, found brass cap out of place and buried. We reset. BTs. OK. This wit. cor. is 13.2 ft. West of true corner.

Douglas County Surveyors Office - Vernon R. Tracy and J. Heritage, crew - July 27, 1973 - C.S. File 56/34-11

Found - 1965 Cadastral brass cap at WITNESS corner, 13.2 ft. West of true corner point.

Now 12" W. Fir S.20°E., 20.5 ft., now dead. Scribe visible.

Now 21" W. Fir S.79°E., 27.1 ft., alive, "BT" scribe visible on unhealed blaze.

New BT - 10" W. Fir S.31°W., 72.5 ft. marked "WC E 1/16 S28 CS BT"

Corner lies 5.0 ft. North of small creek.

BLM resurvey by Lance J. Bishop, Cadastral Surveyor, under Group #1170, surveyed Sept. 1983 - (DCSO records Vol. 47 Page(s) 17838-39)

(19.79 chs.)

True point for the E 1/16 sec. cor. of secs. 21 and 28, at proportionate distance.

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.
$$\begin{array}{r} \text{E } 1/16 \quad \frac{\text{S } 21}{\text{S } 28} \\ 1983 \end{array}$$

from which

A Fir 10" dia., bears N.1½°E., 106 lks. dist. mkd. E 1/16 S21 BT. (Cont. Next Page)

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 360300

PRIMARY CORNER DESCRIPTION East 1/16 betw secs 21 and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Hemlock 20" dia., bears S.50°W., 51½ lks. dist. mkd. E 1/16 S28 BT.

(19.99 chs. S.89°36'W.)

The witness cor. to the E 1/16 sec. cor. of secs. 21 and 28, monumented with an iron post, 2½" dia., firmly set, with top 24" below surface, with brass cap mkd. in 1965

from which the remains of the bearing trees mkd. by Jelley:

A Fir 24" dia., bears N.79°E., 47 lks. dist. with healed blaze.

A Fir snag 12" dia., bears S.20°E., 31 lks. dist., with scribe marks BT visible on partially healed blaze.

and a bearing tree mkd. by Tracy, in 1973:

A Fir 15" dia., bears S.31°W., 110 lks. dist., with healed double blaze.