

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34; 3 & 4 of T31-7

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 17 Page(s) 7230)

 Set post corner to secs. 3, 4, 33 and 34, from which
 A Laurel 24" dia., bears N.25°E., 68 lks. dist.
 A Pine 10" dia., bears S.10°E., 64 lks. dist.
 A Laurel 30" dia., bears S.10°W., 17 lks. dist.
 A Fir 14" dia., bears N.50°W., 105 lks. dist.

GLO survey by Gerald A. Sorrels, U.S. Surveyor, under Special Instructions dated March 1917 - Surveyed Mar/April 1918 (DCSO records Vol. 17 Page(s) 7291-92) (Info. duplicated in Vol. 27 Pgs. 11614-15)

 The sec. cor., located by reference to the old bearing tree. At the exact cor. point, Set an iron post 3 ft. long 2" dia., 24" in the ground, for cor. of secs. 3, 4, 33 and 34, with brass cap mkd.

T30S	R7W
S33	S34
S4	S 3
T31S	
1918	

from which

- A Madrone 10" dia., bears N.41°E., 71 lks. dist. mkd. T30S R7W S34 BT. (New BT)
- A Sugar Pine 20" dia., bears S.7°E., 59 lks. dist. mkd. T31S R7W S3 BT. (Old BT)
- A Madrona 30" dia., bears S.13°W., 19 lks. dist. mkd. T31S R7W S4 BT. (Old BT)
- A Fir 30" dia., bears N.47°W., 97 lks. dist. mkd. T30S R7W S33 BT. (Old BT)

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Jim Halterman, crew - Feb. 1964 - C.S. File 53/40-49

 Found - Brass cap at corner. (1918 GLO cap)
 NE. and SE. BTs OK. SW. BT now stump. NW. BT, not found.

New BTs -14" R.Fir bears S.86°W., 24.7 ft. scribed T31S R7W S4 CS BT.
 7" Myrtle N.10½°W., 12.9 ft. scribed T30S R7W S33 CS BT.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34; 3 & 4 of T31-7

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Douglas Co. Surveyors Office - John M. Powell and crew - Nov. 25, 1966 - C.S. File 54/36-66

Found - GLO brass cap, properly mkd., in 1918.
Orig. 10" now 12" Laurel N.41°E., 46.9 ft. scribe visible "BT"
Orig. 20" Pine, now dead, S.7°E., 38.9 ft., shows scar.
Orig. 30" Laurel, now stump, S.13°W., 12.5 ft., scribe visible.
14" Fir, now dead, S.86°W., 24.7 ft., pitched over, scribe visible.
7" now 9" Myrtle N.10½°W., 12.9 ft., scribe visible.
New BTs -18" D.Fir S.70°E., 32.1 ft. mkd. T31S R7W S3 CS BT.
8" W.Oak S.71°W., 42.8 ft. mkd. T31S R7W S4 CS BT.
This corner lies East of Cow creek Road, approx. 65.0 ft.

Survey by Howard Johnstone, L.S. #498 - For: Roseburg Lumber Co. - Oct. 22, 1984 - M 97-61

Found - 1918 GLO brass cap/iron pipe.
10" Myrtle N.10½°W., 12.9 ft., face rotten.
12" Madrone N.41°E., 46.9 ft., face open.
18" Fir S.70°E., 32.1 ft., snag.
14" Fir S.86°W., 24.7 ft., down.
8" Oak S.71°W., 42.8 ft.
New BT - 7" Fir S.57°E., 14.5 ft.

Mark Smalley - For: Roseburg Resources Co. - January 2000 - M 134-7

Found - 1918 GLO Brass cap on iron pipe.
13" Madrone N.41°E., 46.9 ft. rotten face.
8" Oak S.71°W., 42.8 ft. healed.
11" Fir S.57°E., 14.5 ft. healed.
18" Fir S.70°E., 32.1 ft. down, rotten.
14" Fir S.86°W., 24.7 ft. down, rotten.
10" Myrtle N.10½°W., 12.9 ft. snag.
Scribed- 8" Fir N.23°E., 29.3 ft. "S 34 BT"

DCSO-GIS Corner visitation - 2/2/2004 - Typed: 2/10/2011 - C.S. File 67/33-1

Monument - 2" IP/BC