

PRIMARY CORNER DESCRIPTION Sec Cor for 27, 28, 33 and 34

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 17 Page(s) 7244)

 Set post cor. to secs. 27, 28, 33 and 34, from which
 A Pine 48" dia., bears N.60°E., 33 lks. dist.
 A Pine 8" dia., bears S.60°E., 64 lks. dist.
 A Pine 30" dia., bears S.35°W., 175 lks. dist.
 A Pine 40" dia., bears N.10°W., 114 lks. dist.

GLO survey by Gerald A. Sorrels, U.S. Surveyor, under Group #36, surveyed March/April 1918 - (DCSO records Vol. 17 Pg. 7299) and duplicated info. in Vol. 27 Page 11620)

 The Sec. cor. located by reference to the bearing trees. At the exact cor. point, Set an iron post 3 ft. long 2" dia., 24" in the ground, for cor. to secs. 27, 28, 33 and 34, with brass cap mkd:

T30S	R7W
S28	S27
S33	S34

from which 1918
 A Yellow Pine 30" dia., bears N.2°30'E., 126 lks. dist. mkd. T30S R7W S27 BT. (New BT)
 A Yellow Pine 30" dia., bears S.66°E., 65 lks. dist. mkd. T30S R7W S34 BT. (Old BT)
 A Yellow Pine 36" dia., bears S.35°W., 169 lks. dist. mkd. T30S R7W S33 BT. (Old BT)
 A Yellow Pine 40" dia., bears N.5°W., 140 lks. dist. mkd. T30S R7W S28 BT. (Old BT)

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V. Perron, crew - Nov. 12, 1969 - C.S. 53/40-99

 Found - 1918 GLO brass cap, firmly set in mound of stone and properly marked.
 Orig. 30" now 36" Y.Pine S.66°E., 42.9 ft., alive, shows good scar.
 Orig. 36" Y.Pine, now burned snag, S.35°W., 11.5 ft., no scribe found.
 Orig. 40" now 48" Y.Pine, dying, N.5°W., 77.9 ft., alive, scribe visible. (Rec. 92.4 ft.)
 30" now 32" Y.Pine, dying, N.2½°E., 83.2 ft., scribe visible.
 New BTs -18" Y.Pine S.9°W., 16.7 ft. mkd. T30S R7W S33 CS BT.
 13" Cedar N.74°E., 17.5 ft. mkd. T30S R7W S27 CS BT.
 This corner lies on SW. side of top of spur, ridge sloping S.

(Cont. Next Page)

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Sec Cor for 27, 28, 33 and 34

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Cor. Fd. and used in BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #1007, surveyed Aug. 1980/March 1982 - (DCSO records, Vol. 43 Pg. 16797)

Fd. OK, March 1994 by R. Quimby - M 119-21