

PRIMARY CORNER DESCRIPTION Sec Cor for 21, 22, 27 and 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 17 Page(s) 7245)

-----  
Set post cor. to secs. 21, 22, 27 and 28, from which  
A Fir 10" dia., bears N.62°E., 17 lks. dist.  
A Fir 10" dia., bears S.35°E., 20 lks. dist.  
A Fir 12" dia., bears S.35°W., 10 lks. dist.  
A Fir 6" dia., bears N.40°W., 6 lks. dist.

Cor. Fd. and used in GLO resurvey by Byars, under Contract #450, dated July 28, 1882 - (DCSO rec. Vol. 17 Pgs. 7264-65)

Not Fd, DCSO 3/1965 - C.S. File 53/40-64

BLM resurvey by John Jelley, Cadastral Surveyor, Group #571, surveyed May/June 1965 - (DCSO records Vol. 33 Page(s) 13863-64)

-----  
Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap mkd:  
T 30 S R 7 W  
S 21 | S 22  
S 28 | S 27  
1965

from which  
A W.Fir 16" dia., bears N.58¼°E., 35 lks. dist. mkd. T30S R7W S22 BT.  
A Fir 8" dia., bears S.25°E., 27½ lks. dist. mkd. T30S R7W S27 BT.  
A W.Fir 8" dia., bears S.25½°W., 25½ lks. dist., mkd. T30S R7W S28 BT.  
A W.Fir 10" dia., bears N.23½°W., 29 lks. dist. mkd. T30S R7W S21 BT.

BLM Resurvey by Lance J. Bishop, Cadastral Surveyor - under Group #1170, surveyed Sept. 1983 - (DCSO records Vol. 47 Pgs. 17837-38)

-----  
At sec. cor., monumented with an iron post, 2½" dia., firmly set, projecting 6" above the ground, with 1965 brass cap from which the remains of bearing trees mkd. by Jelley:  
A W.Fir 22" dia., bears N.58¼°E., 35 lks. dist., with healed blaze.  
A Fir stump 8" dia., bears S.25°E., 27½ lks. dist., with downed tree alongside, fragmentary scribe marks visible on partially healed blaze. (Cont. Next Page)

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Sec Cor for 21, 22, 27 and 28

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A W.Fir stump 8" dia., bears S.25½°W., 25½ lks. dist. with  
downed tree alongside.

A W.Fir snag 11" dia., bears N.23½°W., 29 lks. dist., with  
fragmentary scribe marks visible on partially healed  
blaze.

and new bearing trees:

A W.Fir 6" dia., bears S.57½°E., 43 lks. dist. mkd. T30S  
R7W S27 BT.

A W.Fir 6" dia., bears S.10½°W., 105 lks. dist. mkd. T30S  
R7W S28 BT.

A W.Fir 8" dia., bears N.59°W., 161 lks. dist. mkd. T30S  
R7W S21 BT.

Survey by Mark Smalley - For; Roseburg Resources Co. - April  
1993 - C.S. File 63/153-7

-----  
Found - Brass cap with iron pipe.  
Fir 10", N.23½°W., 19.1 ft., snag, scribe visible.  
Fir 22", N.58°E., 23.1 ft., snag, with tag.  
Fir 6", S.50°E., 14.2 ft., down, rotted.  
Fir 6", S.25½°W., 16.8 ft., down, rotted.  
W.Fir 14", S.57½°E., 28.4 ft., good condition,  
healed blazes with tag.  
New BTs -D.Fir 14", N.64°E., 66.3 ft. scribed "S22 BT" w/tag.  
D.Fir 5", S.58°W., 33.5 ft. scribed "S28 BT" w/tag.  
Pine 5", N.26°W., 36.2 ft. scribed "S21 BT" w/tag.  
Steel fence posts were set on line from this corner East to  
the ¼ corner to secs. 22 and 27. Corner lies 200 ft. South  
of Road #27.0, and 450 ft. West of Rd. #28.1.