

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 17 Page(s) 7246)

- 
- Set post cor. to secs. 15, 16, 21 and 22, from which
- A Fir 6" dia., bears N.5°E., 26 lks. dist.
  - A Fir 10" dia., bears S.52°E., 54 lks. dist.
  - A Fir 10" dia., bears S.38°W., 40 lks. dist.
  - A Fir 8" dia., bears N.18°W., 15 lks. dist.

Cor. Fd. and used by Byars in GLO resurvey, under Group #450, surveyed July 28, 1882 - (DCSO records, Vol. 17 Pg. 7255)

BLM resurvey by John Jelley, Cadastral Surveyor, Group #571, surveyed May/June 1965 - (DCSO records Vol. 33 Page(s) 13865-66)

-----

The sec. cor., determined at record bearing and distance from the remaining original bearing trees:

- A W.Fir 35" dia., bears N.5°E., 26 lks. dist., with fragmentary scribe marks visible in negative on section of overgrowth.
- A down and rotted W.Fir 30" dia., bears S.38°W., 40 lks. dist., no marks remaining.

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 30 S R 7 W  
S 16 S 15  
S 21 S 22  
1965

from which new bearing trees:

- A W.Fir 15" dia., bears N.44°E., 47 lks. dist. mkd. T30S R7W S15 BT.
- A Fir 19" dia., bears S.55°E., 41 lks. dist. mkd. T30S R7W S22 BT.
- A W.Fir 9" dia., bears S.53°W., 72 lks. dist. mkd. T30S R7W S21 BT.
- A W.Fir 10" dia., bears N.27°W., 59 lks. dist. mkd. T30S R7W S16 BT.