

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7256)

Set Fir post 3 ft. long, 3" sq., 18" in the ground for ¼ sec. cor. marked ¼ S on W. face, from which

A Yew 7" dia., bears S.80°W., 26 lks. dist. mkd. ¼ S BT

A Fir 14" dia., bears N.82°E., 24 lks. dist. mkd. ¼ S BT

BLM resurvey by John Jelley, Cadastral Surveyor, Group #571, surveyed May/June 1965 - (DCSO records Vol. 33 Page(s) 13867)

The ¼ sec. cor., determined at record bearing and distance from the remaining original bearing tree:

A Fir 33" dia., bears N.82°E., 24 lks. dist. with fragmentary scribe marks visible on partlay opened blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 30 S R 7 W

¼

S 16 S 15

1965

from which a new bearing tree:

A Cedar 18" dia., bears S.48¼°W., 60½ lks. dist., mkd. ¼ S16 BT.