

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9, 10, 15 and 16

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7256)

Set a Laurel post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 9, 10, 15 and 16, marked T30S R7W S10 on NE.; S15 on SE.; S16 on SW.; and S9 on NW. faces with 4 notches on the S. and 3 notches on E. edges, from which

An Oak 9" dia., bears S.76°E., 61 lks. dist., mkd. T30S R7W S15 BT.

A Cedar 14" dia., bears S.20°W., 62 lks. dist. mkd. T30S R7W S16 BT.

No trees in limits on secs.9 and 10. Made stone mound about post 2 ft. high, 4 ft. at base, pits impracticable.

BLM resurvey by John Jelley, Cadastral Surveyor, Group #571, surveyed May/June 1965 - (DCSO records Vol. 33 Page(s) 13868)

The sec. cor., determined at record bearing and distance from the original bearing trees:

An Oak 16" dia., bears S.76°E., 61 lks. dist., with scribe marks BT visible on partly open blaze.

The burned and rotted remains of a Cedar, size indeterminate, bears S.20°W., 62 lks. dist., no marks remaining.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 30 S R 7 W
S 9 S 10
S 16 S 15
1965

from which new bearing trees:

A Pine 20" dia., bears N.52½°E., 273 lks. dist., mkd. T30S R7W S10 BT.

A Cedar 27" dia., bears S.64°W., 305 lks. dist. mkd. T30S R7W S16 BT.

A Cedar 45" dia., bears N.10°W., 98 lks. dist. mkd. T30S R7W S9 BT.

From this point United States Coast and Geodetic Survey triangulation station, Buck Mountain, 1942, bears N.2°13'E., 19.53 chs. dist., monumented with a brass cap, 3½" dia., firmly set in concrete.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #880, surveyed Aug/Oct. 1975 - (DCSO records Vol. 38 Page(s) 15597-98)

(Cont. Next Page)

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9, 10, 15 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

At the sec. cor., monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, and in a mound of stone, 2 ft. base, to top, with 1965 brass cap.

from which the remains of the original bearing trees:

A W.Oak 18" dia., bears S.76°E., 61 lks.dist., no marks visible on decayed blaze.

and bearing trees mkd. by Jelley:

A Pine 23" dia., bears N.53½°E., 273 lks. dist., with scribe marks 30 visible on open blaze.

A Cedar 31" dia., bears S.64°W., 305 lks. dist., with scribe marks T30S R7W S16 BT visible on open blaze.

A double Cedar 50" dia., bears N.10°W., 98 lks. dist., with healed blaze.

and a new bearing tree:

A Fir 18" dia., bears S.68°E., 142½ lks. dist., mkd. T30S R7W S15 BT.

Add marks 1975 to brass cap.