

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7258)

Set stone 13 x 7 x 7 ins., 9" in the ground for the 1/4 sec. cor. marked 1/4 on W. face, from which

A Laurel 7" dia., bears N.40°W., 23 lks. dist. mkd. 1/4 S BT

A Laurel 10" dia., bears S.21°E., 47 lks. dist. mkd. 1/4 SBT

Not fd by DCSO 6/1965 C.S. File 53/40-76

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #880, surveyed Aug/Oct. 1975 - (DCSO records Vol. 38 Page(s) 15598)

Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

1/4
S 9 | S 10
T 30 S R 7 W
1975

from which

A Fir 10" dia., bears N.81°E., 54 1/2 lks. dist. mkd. 1/4 S10 BT.

A Fir 12" dia., bears S.64 1/2°W., 68 lks. dist. mkd. 1/4 S9 BT

Fd. OK, Jan. 13, 1984 by B. Holt - C.S. File 58/290-5