

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7258-59)

Set Laurel post 4 ft. long, 4" sq., 24" in the ground for the cor. to secs. 3, 4, 9 and 10 marked T30S R7W S3 on NE.; S10 on SE.; S9 on SW.; S4 on NW. faces, with 5 notches on S. and 3 notches on E. edges, from which

A Laurel 8" dia., bears N.42°E., 20 lks. dist. mkd. T30S R7W S3 BT.

A Laurel 8" dia., bears S.54°E., 22 lks. dist. mkd. T30S R7W S10 BT.

A Laurel 7" dia., bears S.45°W., 14 lks. dist. mkd. T30S R7W S9 BT.

A Laurel 6" dia., bears N.44°W., 20 lks. dist. mkd. T30S R7W S4 BT.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #880, surveyed Aug/Oct. 1975 - (DCSO records Vol. 38 Page(s) 15599)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 30 S R 7 W
S 4 | S 3
S 9 | S 10
1975

from which

A Fir 9" dia., bears N.3½°E., 31 lks dist. mkd. T30S R7W S3 BT.

A Fir 9" dia., bears S.63°E., 45 lks. dist. mkd. T30S R7W S10 BT.

A Fir 11" dia., bears S.60°W., 45½ lks. dist. mkd. T30S R7W S9 BT.

A Fir 8" dia., bears N.81 3/4°W., 64 lks. dist. mkd. T30S R7W S4 BT.

Fd. OK, Jan. 13, 1984 by B. Holt - C.S. File 58/290-4