

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 4

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7261)

Set a stone 12 x 8 x 8 ins., 8" in the ground for 1/4 sec. cor. marked 1/4 on W. face, from which
A Live Oak 10" dia., bears S.62°E., 35 lks. dist. mkd. 1/4 S BT.
A Live Oak 12" dia., bears S.54°W., 16 lks. dist. mkd. 1/4 S BT.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #880, surveyed Aug/Oct. 1975 - (DCSO records Vol. 38 Page(s) 15601)

The 1/4 sec. cor., monumented with the original sandstone, 12 x 8 x 8 ins., firmly set, 8" in the ground, mkd. 1/4 on W. face, from which the original bearing trees:
A Live Oak 13" dia., bears S.62°E., 35 lks. dist., with axe marks visible on opened blaze.
A Live Oak 12" dia., bears S.45°W., 16 lks. dist., with fragmentary scribe marks visible on opened blaze.
(Rec. S.54°W.)
At the corner point
Set an iron post, 28" long, 2 1/2" dia., 18" in the ground, to bedrock, mkd. X, and in a mound of stone 4 ft. base, to top, with brass cap mkd: 1/4
S 4 S 3
T 30 S R 7 W
from which new bearing trees:
A Fir 10" dia., bears N.69 1/2°E., 83 lks. dist., mkd. 1/4 S3 BT.
A Fir 6" dia., bears N.48°W., 97 lks. dist., mkd. 1/4 S4 BT
Deposit corner stone alongside iron post.