

PRIMARY CORNER DESCRIPTION Sec. Cor for 3 & 4; & 33 & 34, T29½-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - W.H. Byars, under contract # 456 dated July. 28, 1882 (DCSO rec. Vol. 15 Pg. 6550)

-----  
 Set a Pine post, 4½ ft. long, 4" square, 24" in ground for the corner to secs. 3, 4, 33 and 34, marked T29S R7W S34 on the NE. face, T30S S3 on SE. face, S4 on the SW. face and S33 on the NW. face; also, 3 notches on the East and 3 notches on the West angles of the same, and from which,


- A Pine 36" dia., bears N.74°E., 152 lks. dist. marked T29S R7W S34 BT.
- A Pine 4" dia., bears S.25°E., 15 lks. dist. marked T30S R7W S3 BT.
- A Pine 6" dia., bears S.75°W., 5 lks. dist. marked T30S R7W S4 BT.
- A Pine 6" dia., bears N.30°W., 16 lks. dist. marked T29S R7W S33 BT.

GL0 survey by Mensch under Instructions dated April 18, 1924 (DCSO records Vol. 14 Page(s) 6051-52)

-----  
 Intersect the cor. of secs. 3, 4, 33 and 34, which is a pine post 4" sq., 12" above ground, decaying, marked T29S R7W S34 on NE., T30S S3 on SE., S4 on SW. and S33 on NW. faces, with 3 notches on E. and W. edges; from which the original bearing trees:

- A Pine, rotted down, bears N.72°E., 152 lks. dist., (not N.74°E.)
- A Pine 16" dia., bears S.25°E., 5 lks. dist., (not 15 lks.), marks grown over.
- A Pine, rotted down, bears S.15°W., 5 lks. dist., (not S.75°W.)
- A Pine 24" dia., bears N.60°W., 16 lks. dist., (not N.30°W.) marks grown over. I re-mark T29½S R7W S33 BT.

At the exact cor. point, alongside the pine post, Set an Iron post 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 3, 4, 33 and 34, with brass cap marked:



from which new bearing trees:

- A Pine 18" dia., bears N.41°E., 65 lks. dist., marked T29½S R7W S34 BT.
- A Pine 18" dia., bears S.66°W., 39 lks. dist., marked T30S R7W S4 BT.

(Cont. Next Page)

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 400700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3 & 4; 33 & 34, T29½-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - James Byron, Deputy - Dale McFarland; John Powell - June 1962 - C.S. File 49/139-86

-----  
Found - Brass cap at corner.  
SE BT, now stump hole.  
SW BT, now dead.  
NE BT, down.  
NW BT, in poor condition.  
New BTs -9" W.Fir bears S.3°E., 10.8 ft. scribed S3 T30S R7W CS BT.  
6" Fir bears S.70°W., 19.0 ft. scribed S4 CS BT.  
11" Cedar bears N.72°W., 18.7 ft. scribed S33 T29½S R7W CS BT.  
23" Pine bears N.19°E., 25.1 ft. scribed S34 T29½S R7W CS BT.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #880, surveyed Aug/Oct. 1975 - (DCS0 records Vol. 38 Page(s) 15601-02)

-----  
The Sec. cor., perpetuated by Byron in 1962, monumented with an iron pipe, 2" dia., firmly set, projecting 10" above ground, with the remains of the iron post set by Mensch in 1924, alongside, cap mkd. as described in the official record, from which the remains of the original bearing trees:  
A root hole bears S.25°E., 5 lks. dist., with a down Pine alongside, 8" dia., with axe marks visible on decayed blaze.  
A root hole bears S.15°W., 5 lks. dist., with a down Pine alongside 10" dia., with axe marks visible on decayed blaze.  
A Pine 28" dia., bears N.54°W., 16 lks. dist., no marks visible on decayed blaze. (Record, N.60°W.)  
and the remains of bearing trees mkd. by Mensch:  
A root hole bears N.41°E., 65 lks. dist.  
A Pine snag 18" dia., bears S.66°W., 39 lks. dist., with healed blaze.  
and bearing trees mkd. by Byron:  
A Pine 24" dia., bears N.19°E., 38 lks. dist., with fragmentary scribe marks visible on partially open double blaze.  
A W.Fir 10" dia., bears S.6½°E., 16½ lks. dist., with healed double blaze.  
A Fir 8" dia., bears S.70°W., 29 lks. dist., with healed double blaze.  
A Cedar 12" dia., bears N.72°W., 28½ lks. dist., with scribe marks 29½S R7W S33 CS BT visible on open double blaze.  
(Cont. Next Page)

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 400700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3 & 4; 33 & 34, T29½-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

At the corner point  
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground,  
with brass cap mkd:

T 29½ S R 7 W  
S 33 | S 34  
S 4 | S 3  
T 30 S  
1975

from which a new bearing tree;  
A Fir 9" dia., bears N.33°E., 48 lks. dist. mkd. T29½S R7W  
S34 BT.  
Reset old iron post and iron pipe alongside iron post.