

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 17 Page(s) 7246)

Set ¼ sec. post, from which
A Laurel 30" dia., bears S.48°E., 63 lks. dist.
A Laurel 30" dia., bears N.70°W., 55 lks. dist.

Fd. cor. OK, GLO resurvey by Byars, under Contract #450, dated July 28, 1992 - (DCSO records, Vol. 17 Pg. 7258)

Douglas County Surveyors Office - Vernon R. Tracy and Mike Darby, crew - May/June 1965 - C.S. File 53/40-73

Found - Orig. 30" now 35" Laurel, S.48°E., 41.6 ft., shows "BT" on open blaze.
Orig. 30" now 28" Laurel N.70°W., 38.9 ft. S.B. 36.3 ft., shows fragmentary reverse scribe mark.

Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 7 W
S 15
S 22
1965

New BTs -8" D.Fir N.26°E., 80.5 ft. mkd. ¼ S15 CS BT.
9" D.Fir S.45°W., 14.5 ft. mkd. ¼ S22 CS BT.

Cor. Fd. as recorded in 1965 and used in BLM resurvey by John M. Jelley, Cadastral Surveyor, under Group #571, surveyed May/June 1965 - (DCSO records, Vol. 33 Pg. 13866) **Added marks BLM 1965 to brass cap.**